



TP-Link JetStream TL-SG3428MP netværksswitch Administreret L2+ Gigabit Ethernet (10/100/1000) Strøm over Ethernet (PoE) 1U Sort



Mærke : TP-Link

Produktserie: JetStream

Produktkode: TL-SG3428MP

Produkt navn : TL-SG3428MP

TP-Link JetStream TL-SG3428MP. Switch-type: Administreret, Switch lag: L2+. Basis omskiftning RJ-45 Ethernet porttype: Gigabit Ethernet (10/100/1000), Basis omskiftning RJ-45 Ethernet porte, antal: 24, Port til konsol: RJ-45/Micro-USB. MAC adresselabel: 16000 entries, Switch kapacitet: 56 Gbit/sek.. Netværksstandarder: IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z. Strømskik: AC-in jack. Strøm over Ethernet (PoE). Stativ-montering, Formfaktor: 1U




| Administrationsfunktioner | | Sikkerhed | |
|---|---|--|---|
| Switch-type * | Administreret | SSH/SSL support | ✓ |
| Switch lag | L2+ | Loop beskyttelse | ✓ |
| Servicekvalitet support (QoS) | ✓ | BPDU filtrering/beskyttelse | ✓ |
| Webbaseret administration | ✓ | IP-MAC-portbinding | ✓ |
| Cloud-administreret | ✓ | Godkendelse | MAC-baseret godkendelse, Portbaseret godkendelse |
| ARP inspektion | ✓ | | |
| Konfigurerer lokationsindstillinger (CLI) | ✓ | | |
| System hændelseslog | ✓ | | |
| Porte & Grænseflader | | Multicast funktioner | |
| Basis omskiftning RJ-45 Ethernet porte, antal * | 24 | Multicast-understøttelse | ✓ |
| Basis omskiftning RJ-45 Ethernet porttype * | Gigabit Ethernet (10/100/1000) | | |
| Gigabit Ethernet (kobber) porte, antal | 24 | Protokoller | |
| Antal SFP modulslots | 4 | Administrationsprotokoller | SNMPv1/v2c/v3, LLDP/LLDP-MED |
| Port til konsol | RJ-45/Micro-USB | GARP VLAN registreringsprotokol (GVRP) | ✓ |
| Strømskik | AC-in jack | | |
| Netværk | | Design | |
| Netværksstandarder * | IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z | Stativ-montering * | ✓ |
| 10G understøttelse * | ✗ | Formfaktor | 1U |
| Kobber ethernet kabelteknologi | 10BASE-T, 1000BASE-T | Produktfarve | Sort |
| Port-spejlning | ✓ | LED-indikatorer | ✓ |
| IP-routing | ✓ | Antal blæsere | 2 blæser(e) |
| Flowkontrol support | ✓ | Strømstyring | |
| | | Strømkilde * | Vekselstrøm |
| | | Strømforsyning inkluderet * | ✓ |
| | | Vekselstrømsindgangsspænding | 100 - 240 V |
| | | Vekselstrømsindgangsfrekvens | 50/60 Hz |
| | | Strømforgbrug (maks.) | 463,8 W |
| | | Power over Ethernet (PoE) | |
| | | Strøm over Ethernet (PoE) * | ✓ |


| Netværk | | Power over Ethernet (PoE) | |
|------------------------------|---|--|---------------|
| Link aggregering | ✓ | Power over Ethernet plus (PoE+) porte, antal | 24 |
| Broadcast stormkontrol | ✓ | Power over Ethernet (PoE) effekt pr. port | 30 W |
| Begrænsning af hastighed | ✓ | Total Power over Ethernet (PoE) | 384 W |
| Spanning tree protokol | ✓ | Driftsbetingelser | |
| Head-of-line (HOL) blokering | ✓ | Driftstemperatur (T-T) | 0 - 45 °C |
| Ethernet LAN-datahastigheder | 10,100,1000 Mbit/s | Opbevaringstemperatur (T-T) | -40 - 70 °C |
| Aktiv link opdagelse | ✓ | Relativ luftfugtighed ved drift (H-H) | 10 - 90% |
| VLAN understøttelse | ✓ | Relativ luftfugtighed ved opbevaring (H-H) | 5 - 90% |
| Vituelle LAN funktioner | MAC address-based VLAN, Port-based VLAN, Private VLAN, Tagged VLAN, Voice VLAN | Vægt & størrelser | |
| Antal VLAN'er | 4000 | Bredde | 440 mm |
| Dataoverførsel | | Dybde | 330 mm |
| Switch kapacitet * | 56 Gbit/sek. | Højde | 44 mm |
| Hastighed for videresendelse | 41,66 Mpps | Emballage indhold | |
| MAC adresselabel * | 16000 entries | Hurtig start guide | ✓ |
| Opbevar-og-frem | ✓ | Brugervejledning | ✓ |
| Jumbo Frames support | ✓ | Emballeringsdata | |
| Jumbo rammer | 9000 | Pakkebredde | 440 mm |
| Pakke bufferlager | 12 MB | Pakkedybde | 528 mm |
| Sikkerhed | | Pakkehøjde | 100 mm |
| DHCP funktioner | DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping | Pakkevægt | 6,08 kg |
| Adgangskontrolliste (ACL) | ✓ | Godkendelser | |
| IGMP snooping | ✓ | Certificering | CE, FCC, RoHS |
| Sikkerhedsalgoritmer | SSH, SSL/TLS | Logistik data | |
| Filtrering af MAC-adresser | ✓ | Harmoniseret systemkode (HS) | 85176990 |
| Statisk port, sikkerhed | ✓ | | |



6935364010744



0845973010157



845973010157

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.