



## TP-Link JetStream TL-SX3008F netværksswitch Administreret L2/L3 Sort

Mærke : TP-Link

Produktserie: JetStream

Produktkode: TL-SX3008F

Produktnavn : TL-SX3008F



TP-Link JetStream TL-SX3008F. Switch-type: Administreret, Switch lag: L2/L3. Port til konsol: RJ-45/micro-USB. MAC adresselabel: 32000 entries, Switch kapacitet: 160 Gbit/sek.. Netværksstandarder: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Strømkontakt: DC-in-stik. Stativmontering



| Administrationsfunktioner                   |  | Sikkerhed                                   |  |
|---|--|---|--|
| Switch-type *                               | Administreret  | BPDU filtrering/beskyttelse                 | ✓  |
| Switch lag                                  | L2/L3  | IP-MAC-portbinding                          | ✓  |
| Servicekvalitet support (QoS)               | ✓  | Godkendelse                                 | Gæste VLAN, MAC-baseret godkendelse, Portbaseret godkendelse, Webbaseret godkendelse |
| Webbaseret administration                   | ✓  | Godkendelsestype                            | AAA, TACACS+   |
| Cloud-administreret                         | ✓  | Algoritmer for køplanlægning                | SP, WRR+SP, Weighted Round Robin (WRR)   |
| Trafik klassificering                       | ✓  | <b>Multicast funktioner</b>                 |  |
| ARP inspektion                              | ✓  | Multicast-understøttelse                    | ✓  |
| Konfigurerer lokationsindstillinger (CLI)   | ✓  | Multicast Listener Discovery (MLD) snooping | ✓  |
| System hændelseslog                         | ✓  | <b>Protokoller</b>                          |  |
| MIB support                                 | RFC2925, RFC2618, RFC2620, RFC2021, RFC2819, RFC2674, RFC1493, RFC1643, RFC2233, RFC1213 | Administrationsprotokoller                  | SNMPv1/v2c/v3, SNMP  |
| <b>Porte &amp; Grænseflader</b>             |  | IPv4 & IPv6 funktioner                      | IPv6 Telnet, IPv6 ping, IPv6 tracer  |
| Basis omskiftning RJ-45 Ethernet porttype * | ✗  | <b>Design</b>                               |  |
| Antal SFP + modulslots                      | 8  | Stativ-montering *                          | ✓  |
| Port til konsol                             | RJ-45/micro-USB  | Produktfarve                                | Sort   |
| Strømkontakt                                | DC-in-stik   | LED-indikatorer                             | ✓  |
| <b>Netværk</b>                              |  | <b>Strømstyring</b>                         |  |
| Netværksstandarder *                        | IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x            | Strømkilde *                                | Vekselstrøm  |
| 10G understøttelse *                        | ✓  | Strømforsyning inkluderet *                 | ✓  |
| Port-spejling                               | ✓  | Vekselstrømsindgangsspænding                | 220 V  |
| IP-routing                                  | ✓  | Vekselstrømsindgangsfrekvens                | 50/60 Hz   |
| Flowkontrol support                         | ✓  | Strømforbrug (maks.)                        | 15,46 W  |


| Netværk                      |  | Power over Ethernet (PoE)                  |               |
|------------------------------|--|--|---------------|
| Link aggregering             | ✓  | Strøm over Ethernet (PoE) *                | ✗             |
| Broadcast stormkontrol       | ✓  | <b>Driftsbetingelser</b>                   |               |
| Begrænsning af hastighed     | ✓  | Driftstemperatur (T-T)                     | 0 - 45 °C     |
| Spanning tree protokol       | ✓  | Opbevaringstemperatur (T-T)                | -40 - 70 °C   |
| Head-of-line (HOL) blokering | ✓  | Relativ luftfugtighed ved drift (H-H)      | 10 - 90%      |
| VLAN understøttelse          | ✓  | Relativ luftfugtighed ved opbevaring (H-H) | 5 - 90%       |
| Vituelle LAN funktioner      | Private VLAN, Protocol-based VLAN, Voice VLAN                          | Varmeafgivelse                             | 52,75 BUT/t   |
| Antal VLAN'er                | 4000   | <b>Vægt &amp; størrelser</b>               |               |
| <b>Dataoverførsel</b>        |  | Bredde                                     | 440 mm        |
| Switch kapacitet *           | 160 Gbit/sek.  | Dybde                                      | 180 mm        |
| Hastighed for videresendelse | 119,04 Mpps  | Højde                                      | 44 mm         |
| MAC adresselabel *           | 32000 entries  | <b>Emballage indhold</b>                   |               |
| Antal køer                   | 8  | Kabler inkluderet                          | Vekselstrøm   |
| Statisk rute                 | ✓  | Hurtig start guide                         | ✓             |
| Jumbo Frames support         | ✓  | Brugervejledning                           | ✓             |
| Jumbo rammer                 | 9000   | Rack monteringskit                         | ✓             |
| Pakke bufferlager            | 16 MB  | <b>Emballeringsdata</b>                    |               |
| <b>Sikkerhed</b>             |  | Pakketype                                  | Kasse         |
| DHCP funktioner              | DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping | Pakkebredde                                | 528 mm        |
| Adgangskontrol (ACL)         | ✓  | Pakkedybde                                 | 250 mm        |
| IGMP snooping                | ✓  | Pakkehøjde                                 | 80 mm         |
| Sikkerhedsalgoritmer         | HTTPS, SSH, SSH-2, SSL/TLS   | Pakkevægt                                  | 2,37 kg       |
| Filtrering af MAC-adresser   | ✓  | <b>Godkendelser</b>                        |               |
| Statisk port, sikkerhed      | ✓  | Certificering                              | CE, FCC, RoHS |
| SSH/SSL support              | ✓  | <b>Logistik data</b>                       |               |
| Loop beskyttelse             | ✓  | Harmoniseret systemkode (HS)               | 85176990      |



6935364006464



0840030702495



840030702495

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.