



TP-Link Archer AX23 trådløs router Gigabit Ethernet Dual-band (2,4 GHz / 5 GHz) Sort

Mærke : TP-Link

Produktserie: Archer

Produktkode: ARCHER AX23

Produktnavn : Archer AX23

TP-Link Archer AX23. WAN forbindelsestype: RJ-45. Wi-Fi-bånd: Dual-band (2,4 GHz / 5 GHz), Bedste Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN dataoverførsels hastighed (maks): 1800 Mbit/s. Ethernet LAN-grænsefladetype: Gigabit Ethernet, Ethernet LAN-datahastigheder: 10,100,1000 Mbit/s, Netværksstandarder: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Sikkerhedsalgoritmer: 64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK, NAT-funktionalitet: Port Forwarding, Port Triggering, UPnP, DMZ. Produkttype: Bordplade router, Produktfarve: Sort



WAN-forbindelse		Protokoller	
Ethernet WAN *	✓	DHCP-klient	✓
SIM-kort slot *	✗	DHCP-server	✓
WAN forbindelsestype	RJ-45	Universal Plug and Play (UPnP)	✓
Trådløse LAN funktioner		Design	
Wi-Fi-bånd *	Dual-band (2,4 GHz / 5 GHz)	Produktfarve	Sort
Bedste Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Produkttype *	Bordplade router
WLAN dataoverførsels hastighed (maks) *	1800 Mbit/s	Godkendelser	
Wi-Fi-standarder	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Certificering	FCC, CE, RoHS
WLAN dataoverførsels hastighed (første bånd)	574 Mbit/s	Emballage indhold	
WLAN dataoverførsels hastighed (anden bånd)	1201 Mbit/s	Kabler inkluderet	LAN (RJ-45)
Modulation	OFDMA	AC-adapter inkluderet	✓
Netværk		Garantibevis	✓
Ethernet LAN *	✓	Hurtig installationsvejledning	✓
Ethernet LAN-grænsefladetype *	Gigabit Ethernet	Antenne	
Ethernet LAN-datahastigheder	10,100,1000 Mbit/s	Antennedesign *	Ekstern
Netværksstandarder	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antennestik type	SMA
Fuld duplex	✓	Funktioner	
Flowkontrol support	✓	Indbygget processer	✓
Portvideresendelse	✓	Processorfrekvens	1500 MHz
Dynamisk DNS (DDNS)	✓	Processorkerner	2
Statisk rute	✓	Strømstyring	
Antal gæsternetværk (2,4 GHz)	1	Strømkilde type *	DC
		Udgangsspænding	12 V
		Udgangsstrøm	1 A

Netværk		Driftsbetingelser	
Antal gæstenetværk (5 GHz)	1	Driftstemperatur (T-T)	0 - 40 °C
VPN-server	OpenVPN, PPTP	Relativ luftfugtighed ved drift (H-H)	10 - 90%
Porte & Grænseflader		Systemkrav	
Ethernet LAN-porte (RJ-45) *	4	Windows 10, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
DC-in-stik	✓		
Administrationsfunktioner			
Webbaseret administration	✓		
Webbaseret opsætningsguide	✓		
Båndbreddekontrol	✓		
Knap til nulstilling	✓		
WPS trykknop	✓		
Sikkerhed			
Sikkerhedsalgoritmer	64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK		
Firewall	✓	Understøttede Linux-operativsystemer	✓
Gæstegang	✓	Understøttede Mac-operativsystemer	✓
Adgangskontrolliste (ACL)	✓		
IP-adresse filtrering	✓		
URL-filtrering	✓		
System hændelseslog	✓		
Understøttelse af DMZ	✓		
Netværk adresse-oversættelse (NAT)	✓		
NAT-funktionalitet	Port Forwarding, Port Triggering, UPnP, DMZ		
Vægt & størrelser			
Bredde		260,2 mm	
Dybde		135 mm	
Højde		41,6 mm	
Emballeringsdata			
Pakkebredde		500 mm	
Pakkedybde		350 mm	
Pakkehøjde		395 mm	
Pakkevægt		730 g	
Logistik data			
Eksportkontrolklassifikationsnummer (ECCN)		5A992	
Harmoniseret systemkode (HS)		8517,62	



4897098687048



4897098683927



0840030707049



840030707049

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.