



Zebra ZQ63-AUFAE14-00 label printer Direct thermal 203 x 203 DPI 115 mm/sec Wired & Wireless Bluetooth



Brand : Zebra

Product code: ZQ63-AUFAE14-00

Product name : ZQ63-AUFAE14-00

203 DPI, 115 mm/s, 104mm, Bluetooth, 256/512MB, Zebra Link-OS

[Zebra ZQ63-AUFAE14-00 label printer Direct thermal 203 x 203 DPI 115 mm/sec Wired & Wireless Bluetooth:](#)

Always on the edge of innovation, Zebra offers premium RFID mobile printers to give your workers a leading advantage. The ZQ630 Plus RFID rounds out Zebra's ZQ600 Plus Series printers with advanced technology and innovative design that drive productivity, ease-of-use and manageability to a new level. Save time, reduce errors, print and encode RFID labels and tags on the spot with ease. A large color display takes all the guesswork out of printer status. Advanced battery technology and more battery capacity—6600 mAh—power every minute of the longest shift. The instant wake-up feature on Wi-Fi™ or Bluetooth® ensures the ZQ630 Plus RFID never sleeps on the job. And, the ZQ630 Plus RFID is easier to integrate, manage, setup and secure, thanks to Zebra's Link-OS® printer operating system and powerful Print DNA™ suite of applications, utilities and developer tools.

Printing		Performance	
Print technology *	Direct thermal		Code 93, GS1 DataBar, Plessey, Code-128 Codabar Library, QR Code, AZTECCODE, CODABAR (NW-7), Data Matrix, Interleaved 2/5, TLC39, Macro PDF417, UPC-A, EAN128, MaxiCode, EAN13, UPC-E, EAN8, PDF417, Code 39
Maximum resolution *	203 x 203 DPI	Built-in barcodes	
Print speed *	115 mm/sec		
Maximum printing width *	10.4 cm		
Paper handling		Design	
Supported paper width	112 mm	Product colour *	Black
Maximum media length	81.3 cm		
Ports & interfaces		Power	
Connectivity technology *	Wired & Wireless	Power source type	Battery
Ethernet LAN *	✗		
Wi-Fi *	✗		
Bluetooth	✓		
Bluetooth version	4.2		
Bluetooth Low Energy (BLE)	✓		
USB port *	✓		
RS-232 ports	1		
Performance		Battery	
Internal memory	256 MB	Battery technology	Lithium-Ion (Li-Ion)
Flash memory	512 MB	Battery capacity	6600 mAh
		Operational conditions	
		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	10 - 90%
		Operating temperature (T-T)	-20 - 50 °C
		Storage temperature (T-T)	-25 - 65 °C
		Weight & dimensions	
		Width	82.5 mm
		Depth	165.1 mm
		Height	186.7 mm
		Weight	1.1 kg



0663056011392



663056011392



5715063748732

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.