Lindy 30m USB 3.0 Active Extension Pro

Brand : Lindy

Product name : 30m USB 3.0 Active Extension Pro

Product code: 43362

- High performance, active cable that provides an extended 30m connection between a computer and USB 3.0 device
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cable configurations used)
- Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- Easy to use connects to the deviceandrsquo;s existing USB cable (2m maximum)
- 2 year warranty
30m USB 3.0 Active Extension Pro
Lindy 30m USB 3.0 Active Extension Pro. Cable length: 30 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Gold, Product colour: Black, Blue

Features

USB version *	USB 3.2 Gen 1 (3.1 Gen 1)
Connector 1 *	USB A
Connector 2 *	USB A
Connector 1 gender *	Male
Connector 2 gender *	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	24/24/20
Connector material	Nickel
Contact material	Brass
Connector contacts plating	Gold
Cable jacket material	Polyvinyl chloride (PVC)
Conductor material	Tinned copper
Connector housing material	Plastic
Maximum data transfer rate	5000 Mbit/s
Maximum data transfer rate	5 Gbit/s
Product colour *	Black, Blue
Cable type	Round cable
Plug and Play	✔
Transmission medium	Twisted pair

Features

Nominal attenuation	0.064MHz - <0.08dB 0.256MHz - <0.11dB 0.512MHz - <0.13dB 0.772MHz - <0.15dB 1.0MHz - <0.20dB 4MHz - <0.39dB 8MHz - <0.57dB 12MHz - <0.76dB 24MHz - <0.95dB 48MHz - <1.35dB 96MHz - <1.90dB 200MHz - <3.20dB 400MHz - <5.80dB

Weight & dimensions

Cable length *	30 m
Cable diameter	7 mm
Bend radius (min)	3.6 cm
Connector 1 dimensions (WxDxH)	15 x 49 x 8 mm
Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm

Packaging data

Package type	Carton

Packaging content

Quantity per pack *	1 pc(s)

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
Certification	California Proposition 65

Logistics data

Warranty period	2 year(s)

4002888433624

Catalog Object Cloud