



Lindy 30m USB 3.0 Active Extension Pro

Brand : Lindy

Product code: 43362

Product name : 30m USB 3.0 Active Extension Pro

- High performance, active cable that provides an extended 30m connection between a computer and USB 3.0 device
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cable configurations used)
- Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- Easy to use □ connects to the device and s existing USB cable (2m maximum)
- 2 year warranty

30m USB 3.0 Active Extension Pro

Lindy 30m USB 3.0 Active Extension Pro. Cable length: 30 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Gold, Product colour: Black, Blue



Features		Features	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)		0.064MHz - <0.08dB 0.256MHz - <0.11dB 0.512MHz - <0.13dB
Connector 1 *	USB A		0.772MHz - <0.15dB 1.0MHz - <0.20dB
Connector 2 *	USB A		4MHz - <0.39dB 8MHz - <0.57dB
Connector 1 gender *	Male	Nominal attenuation	12MHz - <0.76dB 24MHz - <0.95dB
Connector 2 gender *	Female		48MHz - <1.35dB 96MHz - <1.90dB
Connector 1 form factor	Straight		200MHz - <3.20dB
Connector 2 form factor	Straight		400MHz - <5.80dB
AWG wire size	24/24/20		
Connector material	Nickel	Weight & dimensions	
Contact material	Brass	Cable length *	30 m
Connector contacts plating	Gold	Cable diameter	7 mm
Cable jacket material	Polyvinyl chloride (PVC)	Bend radius (min)	3.6 cm
Conductor material	Tinned copper	Connector 1 dimensions (WxDxH)	15 x 49 x 8 mm
Connector housing material	Plastic	Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm
Maximum data transfer rate	5000 Mbit/s	Packaging data	
Maximum data transfer rate	5 Gbit/s	Package type	Carton
Product colour *	Black, Blue	Packaging content	
Cable type	Round cable	Quantity per pack *	1 pc(s)
Plug and Play	✓	Operational conditions	
Transmission medium	Twisted pair	Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-20 - 60 °C
		Certificates	
		Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
		Certification	California Proposition 65
		Logistics data	
		Warranty period	2 year(s)



4002888433624

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-MAR-2025. Prints or copies of Information are only valid on the printed Publication date