



# Lindy 38432 interface hub Mini DisplayPort 21600 Mbit/s Black

Brand : Lindy

Product code: 38432

Product name : 38432

- Connect 2 HDMI displays to a Mini DisplayPort computer or laptop
  - Expand, duplicate or display independent mDP signals over dual HDMI monitors
  - Supports resolutions up to 2 x 4K 30Hz, and audio up to 7.1CH
  - Compatible with various graphics cards including AMD Eyefinity, NVIDIA Surround and Intel Collage
- Mini DisplayPort to 2 Port HDMI MST Hub, Mini DisplayPort, HDMI Type A, Micro-USB  
Lindy 38432. Host interface: Mini DisplayPort, Hub interfaces: HDMI. Data transfer rate: 21600 Mbit/s, Maximum refresh rate: 30 Hz, Supported video modes: 2160p. Power supply type: USB, Input voltage: 5 V, Input current: 1 A. Width: 254 mm, Depth: 49 mm, Height: 10 mm. Quantity per pack: 1 pc(s), Package width: 174 mm, Package depth: 194 mm



Ports & interfaces		Weight & dimensions	
Host interface *	Mini DisplayPort	Weight	49 g
Hub interfaces *	HDMI	Packaging data	
HDMI ports quantity	2	Quantity per pack	1 pc(s)
HDMI version	2.0	Package width	174 mm
DisplayPort version	1.2	Package depth	194 mm
Ports quantity *	2	Package height	10 mm
DC-in jack	✓	Package weight	59 g
Features		Package type	Polybag
Data transfer rate *	21600 Mbit/s	Packaging content	
Maximum refresh rate	30 Hz	Cables included	Micro-USB
Supported video modes	2160p	Operational conditions	
Maximum resolution (HDMI)	3840 x 2160 pixels	Minimum operating temperature	-20 °C
Product colour	Black	Maximum operating temperature	40 °C
Housing material	Acrylonitrile butadiene styrene (ABS)	Operating temperature (T-T)	-20 - 40 °C
HDCP	✓	Operating temperature (T-T)	-4 - 104 °F
HDCP version	1.4	Storage temperature (T-T)	-40 - 80 °C
HD type	4K Ultra HD	Operating relative humidity (H-H)	5 - 90%
Power		Storage relative humidity (H-H)	5 - 90%
Power supply type	USB	Sustainability	
Input voltage	5 V	Sustainability compliance	✓
Input current	1 A	Technical details	
Weight & dimensions		Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS
Width	254 mm		
Depth	49 mm		
Height	10 mm		



4002888384322

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.