



Lindy 4K30 HDMI and USB over IP System - Decoder

Brand : Lindy

Product code: 38397

Product name : 4K30 HDMI and USB over IP System - Decoder

- Decoder module for the Lindy 4K30 HDMI and USB over IP System
- Allows a wide variety of custom AV and KVM distribution systems to be implemented
- Supports 4K30 HDMI, audio, RS-232, IR remote, LAN, KVM and 3rd party control systems
- Built-in Web GUI browser interface supporting drag and drop operations and image preview
- 2 year warranty

4K30 HDMI and USB over IP System - Decoder

Lindy 4K30 HDMI and USB over IP System - Decoder. Type: AV receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. Connectivity technology: Wired, USB version: 1.1/2.0, USB connector type: USB Type-A. Power source type: DC, Operating voltage: 12 V, Output current: 1 A. Width: 204 mm, Depth: 134 mm, Height: 21.5 mm. Quantity per pack: 1 pc(s), Package width: 245 mm, Package depth: 185 mm



Features		Power	
Type *	AV receiver	Power over Ethernet (PoE)	✓
Maximum resolution *	3840 x 2160 pixels	Operational conditions	
Cable types supported	Cat6	Operating temperature (T-T)	0 - 40 °C
Maximum transfer distance	100 m	Storage temperature (T-T)	-20 - 60 °C
Maximum refresh rate	30 Hz	Operating relative humidity (H-H)	20 - 90%
Infrared (IR) frequency range	20 - 60 kHz	Storage relative humidity (H-H)	20 - 90%
Bandwidth	18 Gbit/s	Weight & dimensions	
HDCP	✓	Width	204 mm
HDCP version	2.2	Depth	134 mm
Product colour	Black	Height	21.5 mm
Ports & interfaces		Weight	760 g
Connectivity technology *	Wired	Packaging data	
Ethernet LAN	✓	Quantity per pack	1 pc(s)
RJ-45 input ports	1	Package width	245 mm
Number of HDMI outputs	1	Package depth	185 mm
HDMI version	2.0	Package height	75 mm
USB ports quantity	4	Package weight	1 kg
USB version	1.1/2.0	Package type	Box
USB connector type	USB Type-A	Packaging content	
Serial ports quantity	1	AC adapter included	✓
Serial interface type	RS-232	Cables included	IR
Remote (IR) input	1	Included power plug types	AU, EU, UK, US
Remote (IR) output	1	Manual	✓
DC-in jack	✓	Mounting kit	✓
Power		Technical details	
Power source type	DC	Sustainability compliance	✓
Operating voltage	12 V		
Output current	1 A		

Technical details

Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
-------------------------	--



4002888383974

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.