

## Lindy 73413 mobile device charger Universal White AC Fast charging Indoor

**Brand :** Lindy **Product code:** 73413

**Product name:** 73413

Lindy 73413. Charger type: Indoor, Power source type: AC, Charger compatibility: Universal. Input voltage: 100 - 240 V, Maximum output voltage: 12 V, AC adapter output current: 3 A. USB 2.0 ports quantity: 1, USB Type-C ports quantity: 1, Fast charging, Power protection features: Over current, Over voltage, Overheating, Short circuit. Product colour: White





Performance		Power	
Charger compatibility *	Universal	Output current (9V)	2 A
Power source type *	AC	Output current (12V)	1.5 A
USB 2.0 ports quantity	1	Power consumption (no load)	0.1 W
USB Type-C ports quantity	1	Average active efficiency	5V 81.39%, 9V 85.48%, 12V 85.48%
Fast charging	✓	Efficiency at low load (10%)	✓
Fast charging technology	Adaptive Fast Charging, Power Delivery	Power plug type	Туре С
Sockets quantity	2	Weight & dimensions	
Socket type	Type C (Europlug)	Width	42.6 mm
Charger type *	Indoor	Depth	28.8 mm
Number of outputs	2 outputs	Height	41 mm
USB Power Delivery (USB PD)	<b>✓</b>	Weight	50 g
USB Power Delivery up to	20 W	Packaging data	
Power protection features	Over current, Over voltage, Overheating, Short circuit	Package width	81 mm
Dani	everneum g, energeneum	Package depth	31.5 mm
Design		Package height	120 mm
Product colour *	White	Package weight	75 g
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)	Package type	Carton
Connector material	Copper	Operational conditions	
Power	COPPS.	Operating temperature (T-T) Storage temperature (T-T)	0 - 25 °C -20 - 70 °C
Input voltage	100 - 240 V	Operating relative humidity (H-H)	0 - 70%
Input frequency	50 - 60 Hz	Storage relative humidity (H-H)	0 - 80%
Input current	0.4 A	, , ,	
Maximum output voltage	12 V	Packaging content	
Minimum output voltage	5 V	AC adapter included	✓
Output voltage accuracy (±)	5%	Manual	✓
AC adapter power	20 W		
AC adapter output current	3 A		

Power		Certificates	
Port 1 output power	18 W	Compliance certificates	CE, REACH, RoHS
Port 2 output power	20 W		
Output current (5V)	3 A		



4002888734134

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.