



Lindy 4 Port USB 3.0 Hub with 3 Quick Charge 3.0 Ports

Brand : Lindy

Product code: 43371

Product name : 4 Port USB 3.0 Hub with 3 Quick Charge 3.0 Ports



- Allows connecting up to 4 USB 3.0 devices with data transfer rates up to 5Gbps to a single USB Type A host port
- Supports Quick Charge 3.0 fast and smart charging of up to 3 connected USB devices like smartphones or tablets
- On/Off switch on each port allows users to manage power consumption of the connected devices
- High-performance 54W Multi-County power supply included
- 2 year warranty

4 Port USB 3.0 Hub with 3 Quick Charge 3.0 Ports

Lindy 4 Port USB 3.0 Hub with 3 Quick Charge 3.0 Ports. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-B, Hub interfaces: USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Data transfer rate: 5000 Mbit/s, Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS), Aluminium. Power supply type: AC, Input voltage: 12 V, Input current: 4.5 A. Width: 140 mm, Depth: 46.6 mm, Height: 25.5 mm. Quantity per pack: 1 pc(s), Package width: 205 mm, Package depth: 132 mm



Ports & interfaces		Weight & dimensions	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-B	Height	25.5 mm
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Weight	114 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	7	Packaging data	
Ports quantity *	8	Quantity per pack	1 pc(s)
DC-in jack	✓	Package width	205 mm
Features		Package depth	132 mm
Data transfer rate *	5000 Mbit/s	Package height	52 mm
Product colour	Black	Package weight	600 g
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium	Package type	Carton
Fast charging	✓	Packaging content	
Fast charging technology	Quick Charge 3.0	AC adapter included	✓
Cable length	1 m	Included power plug types	AU, EU, UK, US
Certification	CE, FCC, RoHS & REACH, CP65	Cables included	USB Type-A to USB Type-B
Power		Manual	✓
Power supply type	AC	Operational conditions	
Input voltage	12 V	Operating temperature (T-T)	-5 - 56 °C
Input current	4.5 A	Operating temperature (T-T)	23 - 133 °F
USB charging port	✓	Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions		Operating relative humidity (H-H)	5 - 95%
Width	140 mm	Other features	
Depth	46.6 mm	Chipset	RTS5411, IP6505T



4002888433716

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.