



Lindy 4 Port HDMI 4K60, USB 3.0 and Audio KVM Switch

Brand : Lindy

Product code: 39313

Product name : 4 Port HDMI 4K60, USB 3.0 and Audio KVM Switch



- Controls four HDMI equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button or keyboard hotkeys
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4 with HDR
- USB 3.0 and 3.5mm stereo audio ports to connect microphone, speakers or headphones
- 2 year warranty

4 Port HDMI 4K60, USB 3.0 and Audio KVM Switch

Lindy 4 Port HDMI 4K60, USB 3.0 and Audio KVM Switch. Keyboard port type: USB, Mouse port type: USB, Video port type: HDMI. HD type: 4K Ultra HD, Maximum resolution: 4096 x 2160 pixels, Video bandwidth: 60 Hz. Product colour: Black, Housing material: Metal. Power source: DC, Input voltage: 5 V, Input current: 3 A. Compliance certificates: Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS



Ports & interfaces		Design	
Number of computers controlled *	4	Push button	✓
Keyboard port type *	USB	Hot keys	✓
Mouse port type *	USB		
Video port type *	HDMI		
HDMI ports quantity	5		
HDMI version	2.0		
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4		
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2		
Console ports *	3.5mm headphone, 3.5mm mic, HDMI, USB A		
Console USB ports quantity	4		
Console HDMI ports quantity	1		
USB connector type	USB Type-A, USB Type-B		
Audio connections	✓		
Headphone outputs	1		
Number of microphone inputs	1		
DC-in jack	✓		
Performance		Display	
HD type *	4K Ultra HD	Built-in display *	✗
Maximum resolution *	4096 x 2160 pixels		
Video bandwidth	60 Hz		
HDCP	✓		
Audio channels	2.0		
HDCP version	2.2		
Design		Power	
Rack mounting *	✗	Power source	DC
		Input voltage	5 V
		Input current	3 A
		Sustainability	
		Sustainability compliance	✓
		Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS
		Operational conditions	
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-10 - 60 °C
		Operating relative humidity (H-H)	5 - 80%
		Storage relative humidity (H-H)	5 - 80%
		Weight & dimensions	
		Width	231 mm
		Depth	108 mm
		Height	23 mm
		Weight	710 g
		Packaging data	
		Package width	292 mm
		Package depth	248 mm

Design		Packaging data	
Product colour *	Black	Package height	55 mm
Housing material	Metal	Package weight	980 g
LED indicators	✓	Package type	Box
		Packaging content	
		Manual	✓
		AC adapter included	✓



4002888393133

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-APR-2025. Prints or copies of Information are only valid on the printed Publication date