

Ernitec 0070-08011 security camera Bulb IP security camera 2592 x 1944 pixels Ceiling



Brand : Ernitec

Product code: 0070-08011

Product name : 0070-08011

- 1/2.8" progressive scan CMOS
- 2592x1944 @ 25/30fps 5MP
- 2.8mm fixed lens
- Smart IR working distance up to 15m
- WDR, 3D DNR, ROI, HLC, BLC, Defog
- Support face, human, vehicle detection and capture
- Built-in 1-ch microphone, 1/1 audio in/out, 1/1 alarm in/out
- Power Supply DC12V / POE (IEEE 802.3af)
- IP66
- 5 Year Warranty

Ernitec Pluto 5MP Mini Dome Camera with 2.8mm Lens & IR 15m, PoE, IP66 - NDAA


[Ernitec 0070-08011 security camera Bulb IP security camera 2592 x 1944 pixels Ceiling:](#)

PLUTO-BX-115IR

Ernitec 0070-08011. Type: IP security camera, Connectivity technology: Wired, Certification: CE/FCC. Mounting type: Ceiling, Product colour: Black, White, Form factor: Bulb. Minimum illumination: 0.03 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 93.4°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"). Focal length range: 2.8 mm

Performance		Video	
Type *	IP security camera	Privacy masking	✓
Connectivity technology *	Wired	Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Wide Dynamic Range (WDR)	✓	Bit rate	200kbps~12Mbps
Infrared (IR) cut-off filter	✓	Back Light Compensation (BLC)	✓
Certification	CE/FCC	Highlight Compensation (HLC)	✓
Design		Smart IR	✓
Form factor *	Bulb	Audio	
Mounting type *	Ceiling	Audio formats supported	G.711
Product colour *	Black, White	Signal-to-Noise Ratio (SNR)	55 dB
Housing material	Metal, Plastic	Built-in microphone	✓
International Protection (IP) code	IP66	Bit rate range	8 - 64 Kbit/s
Camera		Network	
Camera pan control	✓	Ethernet LAN *	✓
Minimum illumination	0.03 lx	Number of users	10 user(s)
Angle of rotation	360°	Streaming method	Unicast
Lens viewing angle, horizontal	93.4°	Storage	
Lens viewing angle, vertical	69.1°	Built-in HDD *	✗
Tilt angle range	0 - 72°	Card reader integrated	✓
Pan range	-45 - 45°	Maximum memory card size	256 GB
Camera shutter type	Electronic	Ports & interfaces	
Camera shutter speed	1/5 ~ 1/20,000 s	Ethernet LAN (RJ-45) ports	1
Adjustment shutter speed	Auto/Manual	Security	
Image sensor		Video motion detection	✓
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Intelligent Video Surveillance (IVS) system features	Face detection, Human detection, Vehicle detection
Sensor type *	CMOS	Mirror	✓
Lens system		Power	
Number of lenses *	1		
Focal length range	2.8 mm		
Fixed focus	✓		
Maximum aperture number	2		

Night vision		Power	
Night vision *	✓	Power source type *	DC, PoE
Night vision distance	15 m	Power consumption (typical)	5 W
LED type	IR	DC output voltage	12
Video		Operational conditions	
Maximum resolution *	2592 x 1944 pixels	Operating temperature (T-T)	-40 - 55 °C
Total megapixels *	5 MP	Weight & dimensions	
Noise reduction	✓	Width	99.6 mm
Noise reduction technology	2D noise reduction, 3D noise reduction	Depth	99.6 mm
		Height	63.3 mm
		Weight	380 g
		Packaging data	
		Package weight	1 kg
		Packaging content	
		Number of cameras *	1



5715063068120

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.