ASUS ProArt Display PA32UCXR computer monitor 81.3 cm (32") 3840 x 2160 pixels 4K Ultra HD LCD Black

Brand : ASUS

Product family: ProArt

Product code: 90LM03H0-B01K70

Product name : Display PA32UCXR

ProArt Display PA32UCXR Professional Monitor – 32-inch, 4K UHD (3840 x 2160), 2,304 zones Mini LED Backlight, Built-in Motorized Colorimeter, Self / Auto Calibration, HDR-10, HLG, Dolby Vision, 99% Adobe RGB, 97% DCI-P3, ΔE < 1, Thunderbolt 4 PD 90W, VESA DisplayHDR 1400, Hardware Calibration, Calman Ready, ColourSpace Integration, Ergonomic Stand, Green Sustainability

5 YIL GARANTİ UZATMA ÜRÜN KAYIT SAYFASI

*Ürününüzü kaydetmek için QR kodu okutunuz.

ASUS ProArt Display PA32UCXR computer monitor 81.3 cm (32") 3840 x 2160 pixels 4K Ultra HD LCD Black:

ProArt Display PA32UCXR

1600 Nits Mini-LED Monitor with Built-in Colorimeter for Ultimate Realism

ASUS ProArt Display PA32UCXR features mini-LED backlighting with 2304-zone local dimming, 1600 nits peak brightness, and up to 1000 nits sustained brightness without partial patch limitation. It boasts an industry-leading Delta E < 1 color difference, and features a built-in motorized flip colorimeter to ensure professional-grade color accuracy. Two Thunderbolt™ 4 ports and a host of other connectivity options enable seamless and efficient creative workflows, making this monitor ideal for content creators.

Display	
Display diagonal *	81.3 cm (32")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	Mini LED
Touchscreen *	✕
Display brightness (peak)	1600 cd/m²
Display brightness (typical)	1000 cd/m²
Response time *	5 ms
Anti-glare screen	✔
Screen shape *	Flat
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	1000000:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.073 billion colours
Pixel pitch	0.1845 x 0.1845 mm
Viewable size, horizontal	70.8 cm
Viewable size, vertical	39.9 cm
Digital horizontal frequency	135 - 135 kHz
Digital vertical frequency	40 - 60 Hz
High Dynamic Range (HDR) supported	✔
High Dynamic Range (HDR) technology	DisplayHDR 1400, Dolby Vision, High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)
Colour gamut standard	DCI-P3

Ports & interfaces	
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Thunderbolt 4 ports quantity	2
Headphone out *	✔
Headphone outputs	1
HDCP	✔
HDCP version	2.2

Ergonomics	
VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Wall mountable	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Adjustable height (max)	10 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-30 - 30°
Tilt adjustment	✔
Tilt angle range	-5 - 23°

Power	
Energy efficiency class (SDR) *	G
Energy efficiency class (HDR) *	G
Energy consumption (SDR) per 1000 hours *	41 kWh

Display	
Colour gamut	97%
sRGB coverage (typical)	100%

Performance	
VESA Adaptive Sync support	✔
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia	
Number of speakers	2
RMS rated power	6 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design	
Product colour *	Black
Feet colour	Black

Ports & interfaces	
Built-in USB hub *	✔
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	90 W
HDMI *	✔
HDMI ports quantity	2

Power	
Energy consumption (HDR) per 1000 hours *	63 kWh
Power consumption (typical) *	46.62 W
Power consumption (off)	0 W
Power consumption (PowerSave)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Weight & dimensions	
Width (with stand)	727 mm
Depth (with stand)	245 mm
Height (with stand)	601 mm
Weight (with stand)	13.8 kg
Width (without stand)	727 mm
Depth (without stand)	90 mm
Height (without stand)	445 mm
Weight (without stand)	9.2 kg

Packaging data	
Package width	965 mm
Package depth	228 mm
Package height	555 mm
Package weight	20.5 kg
Package type	Box

Other features	
Hardware calibration	✔

4711387267103

0197105146303

197105146303

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-SEP-2026. Prints or copies of Information are only valid on the printed Publication date