

Lindy 0.8m USB 4 240W Type C Cable, Anthra Line

Brand : Lindy **Product code:** 36956

Product name: 0.8m USB 4 240W Type C Cable, Anthra

Line

- Professional choice USB 4 Gen 3x2 Type C to C cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 40Gbps (backwards compatible to USB 3.2 , USB 2.0 and Thunderbolt 3)
- Supports USB Power Delivery up to 240 Watt and DisplayPort 2.0 Alternate Mode with single 8K or dual 4 K @ 60 Hz
- Triple shielded coaxial cable, gold plated contacts and nickel plated connectors
- 2 year warranty


0.8m USB 4 240W Type C Cable, Anthra Line

Lindy 0.8m USB 4 240W Type C Cable, Anthra Line. Cable length: 0.8 m. Connector 1: USB C, Connector 2: USB C, USB version: USB4 Gen 3x2, Maximum data transfer rate: 40 Gbit/s, Connector contacts plating: Gold, Product colour: Black





Features		Features	
Connector 1 *	mector 1 * USB C mector 2 * USB C mector 1 gender * Male mector 2 gender * Male mector 2 form factor Straight swire size 23/30/34 mector material Nickel mector contacts plating Gold e jacket material Thermoplastic elastomer (TPE) ductor material Copper mector shielding ✓ mector shield material Copper imum data transfer rate 40000 Mbit/s imum data transfer rate 40 Gbit/s luct colour * Black e type Round cable	Maximum refresh rate	60 Hz
		Weight & dimensions	
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size		Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	0.8 m 4.8 mm 2.88 cm 30 x 12.4 x 6.5 mm 30 x 12.4 x 6.5 mm
Connector material		Packaging content	
Connector contacts plating		Quantity per pack *	1 pc(s)
Cable jacket material		Sustainability	
Connector shielding		Sustainability compliance Sustainability certificates	✓ UL ECOLOGO
Maximum data transfer rate		Operational conditions	
Maximum data transfer rate Product colour *		Operating temperature (T-T) Storage temperature (T-T)	-20 - 40 °C -40 - 80 °C
Cable type		Certificates	
Plug and Play USB Power Delivery (USB PD) USB Power Delivery revision USB Power Delivery up to Maximum resolution 3.1 240 W 3840 x 2160 pixels	✓ 3.1	UN number Compliance certificates Certification	REACH, RoHS RoHS, REACH, California Proposition 65 & UL
	3840 x 2160 pixels	Logistics data	
		Warranty period	2 year(s)



4002888369565

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.