



## HP Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

**Brand :** HP Poly

**Product code:** 9W1A6AA

**Product name :** Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

[HP Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom:](#)

### Harness the power of focus

Keep presentations engaging with the Poly Studio E60 smart MPTZ optical zoom camera. The main presenter is always in frame, and every person in the room is shown with exceptional accuracy, even at the far end. With every detail captured, presentations are easier to follow.

HP Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom. Megapixel (approx.): 8 MP. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels, Supported video modes: 2160p, Maximum frame rate: 60 fps. Optical zoom: 12x. Product colour: Black



<b>Camera</b>		<b>System requirements</b>	
Megapixel (approx.) *	8 MP	Windows operating systems supported	✓
Second camera resolution	8 MP	Other operating systems supported	Android
Zoom capability	✓	Mobile operating systems supported	Android
Optical zoom	12x	<b>Performance</b>	
Horizontal field of view	71°	Bundled software	Poly Lens
PTZ control	✓	Cable lock slot	✓
<b>Video</b>		Cable lock slot type	Kensington
HD type *	4K Ultra HD	<b>Technical details</b>	
Maximum video resolution *	3840 x 2160 pixels	Pallet gross weight	378 kg
Maximum frame rate *	60 fps	Total carbon footprint (kg of CO2e)	110
Supported video modes	2160p	<b>Network</b>	
<b>Design</b>		Ethernet LAN data rates	10,100,1000 Mbit/s
Product colour *	Black	<b>Logistics data</b>	
Country of origin	China	UNSPSC-code	45121520
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
Power over Ethernet plus (PoE+) ports quantity	1	Width	200 mm
Ethernet LAN (RJ-45) ports	1	Depth	150 mm
<b>Power</b>		Height	165 mm
Power source type	AC, DC, PoE	Weight	1.79 kg
AC input voltage	12 V	<b>Packaging data</b>	
DC input voltage	12 V	Package width	295 mm
<b>Operational conditions</b>		Package depth	245 mm
Operating temperature (T-T)	0 - 40 °C	Package height	242 mm
Storage temperature (T-T)	-40 - 70 °C	Package weight	3.99 kg
<b>Packaging content</b>			
Warranty card	✓		



0198122304370



198122304370



0198122304387



198122304387



0199642197640



199642197640

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.