

ASUS ProArt PA32UCE computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LED Black

Brand : ASUS

Product family: ProArt

Product code: 90LM03H0-B02K70

Product name : PA32UCE

- 31.5-inch 4K (3840 x 2160) LuxPixel™ AGLR display with 178° wide-view IPS panel
- Wide 98% DCI-P3 and 100% sRGB gamut to meet international color standards along with industry-leading Delta E < 1 color accuracy
- Built-in colorimeter supports Self / Auto calibration, as well as Calman and Light Illusion ColourSpace CMS professional calibration software
- ASUS Light Sync solution with Ambient Light Sensor and Backlight Sensor to ensure reliable color performance
- Extensive connectivity including DisplayPort™ over USB-C® with 96-watt Power Delivery, DisplayPort™ (Daisy-chaining), HDMI® and USB hub
- Built-in Auto KVM allows for effortless switching between two connected laptops or PCs with a single keyboard and mouse
- Eco-friendly with sustainable paper packaging and energy-efficient performance

ProArt Display PA32UCE Professional 4K Monitor (32 inches, 3840 x 2160 LuxPixel AGLR, IPS Panel, HDR-10, 600 nits, 98% DCI-P3, Delta E <1 color accuracy, Light Sync, USB-C, DisplayPort, HDMI)



Display		Ports & interfaces	
Display diagonal *	80 cm (31.5")	DisplayPorts quantity	2
Display resolution *	3840 x 2160 pixels	DisplayPort version	1.4
HD type *	4K Ultra HD	Headphone out *	✓
Native aspect ratio *	16:9	Headphone outputs	1
Display technology *	LED	Headphone connectivity	3.5 mm
Panel type *	IPS	Built-in KVM switch	✓
LED backlight	✓	HDCP	✓
Touchscreen *	✗	HDCP version	2.2
Display brightness (peak)	600 cd/m²	Ergonomics	
Display brightness (typical)	600 cd/m²		
Response time *	5 ms		
Response time measurement type	GTG (Gray to Gray)		
Anti-glare screen	✓		
Screen shape *	Flat		
Contrast ratio (typical) *	1000:1		
Maximum refresh rate *	60 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	1.073 billion colours		
Pixel pitch	0.182 x 0.182 mm		
Pixel density	140 ppi		
Viewable size, horizontal	69.7 cm		
Viewable size, vertical	39.2 cm		
Digital horizontal frequency	15 - 135 kHz		
Digital vertical frequency	48 - 60 Hz		
High Dynamic Range (HDR) supported	✓		
		Power	
		Energy efficiency class (SDR) *	D

Display		Power	
High Dynamic Range (HDR) technology	DisplayHDR 600, High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)	Energy efficiency class (HDR) *	G
Colour depth	10 bit	Energy consumption (SDR) per 1000 hours *	21 kWh
Colour gamut standard	DCI-P3, sRGB	Energy consumption (HDR) per 1000 hours *	34 kWh
sRGB coverage (typical)	100%	Power consumption (typical) *	25.64 W
DCI-P3 coverage	98%	Power consumption (standby) *	0.5 W
Performance		Power consumption (off)	0 W
NVIDIA G-SYNC *	✗	Power consumption (PowerSave)	0.5 W
AMD FreeSync *	✗	AC input voltage	100 - 240 V
VESA Adaptive Sync support	✓	AC input frequency	50/60 Hz
Flicker-free technology	✓	Power supply type	Internal
Low Blue Light technology	✓	Energy efficiency scale	A to G
Multimedia		Weight & dimensions	
Number of speakers	2	Width (with stand)	714.2 mm
RMS rated power	4 W	Depth (with stand)	240 mm
Built-in speaker(s) *	✓	Height (with stand)	617.9 mm
Built-in camera *	✗	Weight (with stand)	8.9 kg
Design		Width (without stand)	714.2 mm
Market positioning *	Graphics design	Depth (without stand)	46.8 mm
Product colour *	Black	Height (without stand)	438.2 mm
Detachable stand	✓	Weight (without stand)	5.8 kg
Feet colour	Black	Packaging data	
Ports & interfaces		Package width	900 mm
Built-in USB hub *	✓	Package depth	162 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package height	515 mm
USB Type-A downstream ports quantity	2	Package weight	14.1 kg
USB Type-C downstream ports quantity	1	Package type	Box
USB Type-C DisplayPort Alternate Mode	✓	Packaging content	
USB Power Delivery (USB PD)	✓	Stand included	✓
USB Power Delivery up to	96 W	Sustainability	
HDMI *	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold, Forest Stewardship Council (FSC) Mix
HDMI ports quantity	2	Other features	
HDMI version	2.1	Certification	Energy Star EPEAT Gold TÜV Flicker-free TÜV Low Blue Light VESA DisplayHDR 600 Calman Ready FSC MIX Mac Compliance



4711387717479



0197105717466



197105717466



0197105717473



197105717473

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.