

ernitec

## Ernitec 0070-24143-HB3000-INDOOR Signage Display 109.2 cm (43") LCD 3000 cd/m<sup>2</sup> 4K Ultra HD



Brand : Ernitec

Product code: 0070-24143-HB3000-INDOOR

Product name : 0070-24143-HB3000-INDOOR

- 4K HD Solution
- 7/24 working Status Security monitor
- High brightness, High contrast, High definition
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178 ° wide viewing angle
- Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation
- Humanize Menu
- Convenient Controller
- HDMI cable included
- 5 Year Warranty

43" 24/7 4K UHD Monitor - High Brightness 3000 NITS - Indoor - Landscape  
Ernitec 0070-24143-HB3000-INDOOR. Display diagonal: 109.2 cm (43"), Display technology: LCD,  
Display resolution: 3840 x 2160 pixels, Display brightness: 3000 cd/m<sup>2</sup>, HD type: 4K Ultra HD



Display		Power	
LED backlight	✓	Power consumption (typical) *	100 W
Display diagonal *	109.2 cm (43")	AC input voltage	100-240 V
Display technology *	LCD	AC input frequency	50-60 Hz
Display resolution *	3840 x 2160 pixels	Weight & dimensions	
Display brightness *	3000 cd/m <sup>2</sup>	Width	972 mm
HD type *	4K Ultra HD	Depth	88 mm
Touchscreen *	✗	Height	576 mm
Native aspect ratio	16:9	Weight	20 kg
Response time	5 ms	Packaging data	
Contrast ratio (typical)	4000:1	Package width	1085 mm
Viewing angle, horizontal	178°	Package depth	232 mm
Viewing angle, vertical	178°	Package height	680 mm
Display number of colours	1.073 billion colours	Package weight	22 kg
Pixel pitch	0.2451 x 0.2451 mm	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	-30 - 85 °C
HDMI ports quantity *	3	Certificates	
HDMI version	2.0	Certification	EMC Class A
DisplayPorts quantity *	1	Features	
USB ports quantity	1	Wall mountable	✓
Audio		Other features	
RMS rated power	6 W	Display brightness (peak)	3000 cd/m <sup>2</sup>
Design		Quick start guide	✓
VESA mounting *	✓	3D	✓
Panel mounting interface	200 x 200 mm	AC (power) in	✓
Performance		Aspect ratio	16:9
Analog signal format system	PAL	Power consumption (average)	120 W
On Screen Display (OSD) languages	English	Brightness	3000 cd/m <sup>2</sup>
Mean time between failures (MTBF)	50000 h	Package dimensions (WxDxH)	1085 x 232 x 680 mm
		Dimensions (WxDxH)	972 x 88 x 576 mm



5715328081550

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.