

ernitec

Ernitec 0070-08128 security camera IP security camera Indoor & outdoor 2592 x 1944 pixels Ceiling/Pole



Brand : Ernitec

Product code: 0070-08128

Product name : 0070-08128

- Four 5MP 1/2.8" STARVIS CMOS image sensor
 - 4 adjustable lenses in one camera, each lens up to 5 MP (2592 × 1944) @25/30 fps
 - 2.7 to 13.5 mm motorized lens
 - Smart IR distance up to 40 m
 - True WDR, 3D DNR, ROI, HLC, BLC, Defog
 - Support face, human, vehicle detection and capture
 - Intelligent analytics: intrusion, single line crossing, double line crossing, loitering, wrong-way, illegal parking, enter area, leave area, and smart motion detection and people counting
 - Built-in microphone, 1/1 audio in/out, 4/2 alarm in/out
 - Built-in SD card slot, up to 1TB
 - IP67, IK10
 - 5 Year Warranty
- Saturn Ultra 5MP Panorama Camera with 4 x 2.7-12mm Motorized Lens & IR 40m, PoE+, IP67, IK10 - NDAA

Ernitec 0070-08128 security camera IP security camera Indoor & outdoor 2592 x 1944 pixels Ceiling/Pole:

Saturn-UX-508IR
Wall Mount Bracket Included

Performance		Audio	
Type *	IP security camera	Audio output channels	1.0 channels
Placement supported *	Indoor & outdoor	Built-in microphone	✓
Connectivity technology *	Wired	Network	
Wide Dynamic Range (WDR)	✓	Ethernet LAN *	✓
Day/night mode	✓	Wi-Fi *	✗
Alarm input/output	✓	Storage	
Design		Card reader integrated	✓
Mounting type *	Ceiling/Pole	Maximum memory card size	1 TB
Product colour *	White	Security	
Housing material	Metal	Alarm input channels	4
International Protection (IP) code	IP67	Alarm output channels	2
IK code	IK10	Management features	
Weatherproof	✓	Reset button	✓
Camera		Power	
Lens viewing angle, horizontal	95.6° to 26.9	Power source type *	PoE+
Lens viewing angle, vertical	65.4° to 20.5	Power consumption (max)	25.3 W
Lens system		Power over Ethernet (PoE)	✓
Focal length range	2.7 - 13.5 mm	Operational conditions	
Fixed focus	✓	Operating temperature (T-T)	-40 - 60 °C
Night vision		Operating relative humidity (H-H)	10 - 90%
Night vision *	✓	Weight & dimensions	
Night vision distance	40 m	Width	2820 mm
LED type	IR	Depth	2820 mm
Infra-red wavelength	850 nm	Height	2063 mm
Video		Weight	4 kg
Maximum resolution *	2592 x 1944 pixels	Packaging data	
Total megapixels *	5 MP	Package weight	4.5 kg
Video intelligence analytic	✓		

Audio

Audio input channels 1.0 channels

Other features

Warranty period 5 year(s)

Technical details

Voltage 12 V



5715328154940

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.