

ernitec

Ernitec 0070-08316-V2 security camera IP security camera Indoor & outdoor Ceiling/Wall/Pole

Brand : Ernitec

Product code: 0070-08316-V2

Product name : 0070-08316-V2

- 2592x1944 @ 25/30fps (5MP)
 - 1/2.8" progressive scan CMOS
 - Min. illumination Color: 0.07 Lux @ (F1.6, AGC ON) B/W: 0.007 Lux, 0 Lux (IR LED ON)
 - Support face, human and vehicle detection and capture
 - Intelligent Analysis: intrusion, single line crossing, double line crossing, loitering, wrong way, illegal parking, people counting
 - Auto tracking and perimeter protection based on deep learning
 - Power Supply AC24V/DC36V/PoE+ (IEEE 802.3at)
 - IP66, TVS4000V. Operating temp: -40°C ~ 55°C
 - Wall Mount included.
 - 5 Year Warranty
- Jupiter Pro 5MP PTZ Camera with 30x Optical Zoom & IR 150m, PoE+, IP66 - NDAA



Ernitec 0070-08316-V2 security camera IP security camera Indoor & outdoor Ceiling/Wall/Pole:

Jupiter-PX-825IR

Performance		Video	
Type *	IP security camera	Total megapixels *	5 MP
Placement supported *	Indoor & outdoor	Video intelligence analytic	✓
Connectivity technology *	Wired	Noise reduction	✓
PTZ control	✓	Noise reduction technology	3D noise reduction
Auto-tracking	✓	3D NR (Noise Reduction)	✓
Wide Dynamic Range (WDR)	✓	Privacy masking	✓
Day/night mode	✓	Back Light Compensation (BLC)	✓
Alarm input/output	✓	Highlight Compensation (HLC)	✓
Design		Audio	
Mounting type *	Ceiling/Wall/Pole	Audio input channels	1.0 channels
Product colour *	White	Audio output channels	1.0 channels
Housing material	Metal	Audio formats supported	G.711
International Protection (IP) code	IP66	Network	
Weatherproof	✓	Ethernet LAN *	✓
Fog proof	✓	Wi-Fi *	✗
Camera		Storage	
Camera pan control	✓	Card reader integrated	✓
Camera tilt control	✓	Compatible memory cards	SD
Minimum illumination	0.07 lx	Maximum memory card size	256 GB
Lens viewing angle, horizontal	56.62° ~ 2.48	Ports & interfaces	
Lens viewing angle, vertical	42.76° ~ 1.91	Ethernet LAN (RJ-45) ports	1
Tilt preset speed	90 °/sec	Security	
Tilt manual speed	0.1 - 90 °/sec	Alarm input channels	2
Pan range	0 - 360°	Alarm output channels	2
Pan preset speed	180 °/sec	Password protection	✓
Pan manual speed	0.1 - 180 °/sec	Management features	
White balance	Auto	Web-based management	✓
Camera shutter type	Electronic	Web browser	✓
Camera shutter speed	1/5 ~ 1/20,000 s	Firmware upgradeable	✓
Image sensor		Reset button	✓
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")		
Sensor type *	CMOS		

Image sensor		Management features	
Number of effective pixels (H x V)	2592 x 1944 pixels	Remotely operated	✓
Lens system		Power	
Zoom capability	✓	Power source type *	PoE+
Optical zoom	30x	AC input voltage	24/36 V
Digital zoom	16x	Power consumption (max)	30 W
Detect distance	150 m	Power over Ethernet (PoE)	✓
Focal length range	5.3 - 159 mm	Operational conditions	
Auto focus	✓	Operating temperature (T-T)	-40 - 55 °C
Night vision		Operating relative humidity (H-H)	0 - 90%
Night vision *	✓	Weight & dimensions	
Night vision distance	150 m	Weight	3.5 kg
B/W night vision distance	150 m	Packaging data	
LED type	IR	Package weight	5 kg
Infra-red wavelength	850 nm	Other features	
		Dimensions (WxDxH)	173.2 x 173.2 x 292.6 mm
		Warranty period	5 year(s)
		Technical details	
		Number of video streams	3



5715328164062

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.