ᐸᴵᴵᴵᴵ, ZEBRA

Zebra DS2208-SR7U3200SGW barcode reader Handheld bar code reader 1D/2D LED Black

Brand : Zebra

Product name : DS2208-SR7U3200SGW

Product code: DS2208-SR7U3200SGW

DS2208 Handheld Scanner USB KIT: DS2208-SR00007ZZWW Scanner, CBA-U32-C09ZAR cable

Zebra DS2208-SR7U3200SGW barcode reader Handheld bar code reader 1D/2D LED Black:

AFFORDABILITY AND SIMPLICITY DELIVERED
2D barcodes have made their way to your Point of Sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards.

Your 1D scanner can't capture the new 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store.

But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. And you can choose the model that best fits your POS needs — the corded DS2208 or the cordless DS2278. The DS2200 Series — the affordability your budget demands, with the deployment, ease of use and management simplicity your business requires.

Scanning

Type *	Handheld bar code reader
Scanner type *	1D/2D
Sensor type *	LED
Linear (1D) barcodes supported *	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar Expanded, Interleaved 2 of 5, MSI, U.P.C.
2D (matrix & stacked) barcodes supported *	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, PDF417, TLC-39
Optical sensor resolution (W x H)	640 x 480 pixels
Working distance	36.8 cm
Wavelength	645 nm
Tilt reading angle	-65 - 65°
Pitch reading angle	-65 - 65°
Yaw reading angle	-65 - 65°
Motion tolerance (cm/s)	13

Ports & interfaces

Connectivity technology *	Wired
Standard interfaces *	USB, RS-232, RS-485, Keyboard wedge

Performance

International Protection (IP) code	IP42
LED indicators	✔
Product colour *	Black

Performance

Certification	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B

Power

Power source type *	DC
Battery life	100 h
AC adapter output voltage	5 V
Power consumption	250 mA

Weight & dimensions

Width	66 mm
Depth	99 mm
Height	165 mm
Weight *	161.6 g

Packaging data

Cables included	Micro-USB
Charging base	✘

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	2400 mAh

Technical details

Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	84716070

5704174886624

8596375197442

Catalog Object Cloud