

Zebra DS4678-DPE Handheld Scanner

Brand : Zebra

Product code: DS4678-DPE0007VZRW

Product name : DS4678-DPE Handheld Scanner



- Scan Type: 2D, 1D
- Image Sensor: 1280x800 pixels
- Scan Range: High Density, Direct Part Marks
- Corded/Cordless: Cordless
- Battery Capacity: 13 hours (2,500 mAh)

Handheld, LED, 1D/2D, 1280x800, High Density, Direct Part Marks, Area imager, Electronics DPM, cordless, white illumination, Twilight Black, vibration, 13 hours (2,500 mAh), 16.8 x 6.6 x 10.7 cm, 225 g

Zebra DS4678-DPE Handheld Scanner:

The cordless DS4678-DPE is purpose built to capture whatever type of barcodes are found in your electronics manufacturing operations-from laser etched direct part marks, high density and low contrast codes, to 4-inch wide barcodes. It's battery delivers more than 50,000 scans in a single charge.

Scanning		Performance	
Type *	Handheld bar code reader	Built-in processor	✓
Scanner type *	1D/2D	Processor frequency	800 MHz
Sensor type *	LED	Product colour *	Black
Linear (1D) barcodes supported *	Codabar, Code 11, Code 128, Code 39, Code 93, EAN 128, EAN 2, EAN 5, EAN-13, EAN-8, GS1 DataBar, MSI-Plessey, U.P.C., UPC-A, UPC-E, UPC-E0, UPC-E1	Vibration function	✓
	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39	Power	
2D (matrix & stacked) barcodes supported *		Power source type *	Battery
Optical sensor resolution (W x H)	1280 x 800 pixels	Number of reads per charge	50000
Horizontal field of view	31.6°	Charging time	2.25 h
Vertical field of view	22.6°	Weight & dimensions	
Light levels (direct sunlight)	0 - 107000 lx	Width	66 mm
Tilt reading angle	0 - 360°	Depth	107 mm
Pitch reading angle	-60 - 60°	Height	168 mm
Yaw reading angle	-60 - 60°	Weight *	225 g
Ports & interfaces		Operational conditions	
Connectivity technology *	Wireless	Operating temperature (T-T)	0 - 50 °C
Standard interfaces *	Bluetooth	Storage temperature (T-T)	-40 - 70 °C
Bluetooth version	5.2	Operating relative humidity (H-H)	5 - 95%
Bluetooth Low Energy (BLE)	✓	Storage relative humidity (H-H)	5 - 95%
		Drop resistance	1.8 m
		Battery	
		Battery technology	Lithium-Ion (Li-Ion)
		Battery capacity	2500 mAh

Performance

International Protection (IP) code	IP52
LED indicators	✓
Image formats supported	BMP, JPEG, TIFF

Technical details

Warranty period	3 year(s)
Compliance certificates	Federal Communications Commission (FCC), Trade Agreements Act (TAA)

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.