## Epson TM-T70II 180 x 180 DPI Wired Thermal POS printer

Brand : Epson Product code: C31CD38032A0

Product name: TM-T70II

Themal Line, 250 mm/sec, ANK, 180x180 DPI, 80 mm, 56/42, Black, 24V, 1.7 kg
Epson TM-T70II. Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI.
Maximum roll diameter: 8.3 cm, Supported paper width: 79.5 mm, Maximum printing width: 7.95 cm.
Connectivity technology: Wired, USB connector: USB Type-B, Standard interfaces: Serial, USB 2.0. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.7 million cuts. Product colour: Grey



Printing		Operational conditions	
Maximum resolution Print speed Character density Print technology * Type *	180 x 180 DPI 250 mm/sec 20 cpi Thermal POS printer	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 45 °C -10 - 50 °C 10 - 90% 10 - 90%
Paper handling		Weight & dimensions	105
Maximum roll diameter Supported paper width Maximum printing width	8.3 cm 79.5 mm 7.95 cm	Width Depth Height Weight	125 mm 194 mm 114 mm 1.7 kg
Ports & interfaces		Packaging data	
USB port * USB 2.0 ports quantity USB connector Serial interface * Connectivity technology *	✓ 1 USB Type-B ✓ Wired	Quantity per pack Package width Package depth Package height Package weight	1 pc(s) 192 mm 253 mm 240 mm 2.6 kg
Serial ports quantity	1	Logistics data	
Standard interfaces  Network  Ethernet LAN *  Wi-Fi *	Serial, USB 2.0  X  X	Harmonized System (HS) code Products per pallet Products per pallet layer Pallet gross width	84433210 112 pc(s) 16 pc(s) 80 cm 120 cm
Features		Pallet gross length Pallet gross height	181.6 cm
Sound pressure level (printing) Mean time between failures (MTBF) Autocutter durability Country of origin Safety	1.7 million cuts China EN, TÜV, GOST-R	Products per pallet (UK) Products per pallet layer (UK) Pallet width (UK) Pallet length (UK) Pallet height (UK)	168 pc(s) 24 pc(s) 100 cm 120 cm 181.6 cm
Certification	CE, GOST-R, EN55022	Other features	
Design		Buffer size	4 KB
Product colour *	Grey	LED indicators	✓
Power Power source type * AC input voltage Power consumption	AC 24 V 2000 mA	Mean cycles between failures (MCBF)	65000000



8715946536644

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.