

## Epson TM-L90-i label printer Direct thermal 180 x 180 DPI 150 mm/sec Wired

**Brand :** Epson

**Product code:** C31C412412

**Product name :** TM-L90-i

150 mm/sec, 180 Dpi, USB 2.0, 1600g

[Epson TM-L90-i label printer Direct thermal 180 x 180 DPI 150 mm/sec Wired:](#)

### Intelligent label printer

Print thermal labels directly from devices running popular web browsers - no drivers needed.

### Epson TM-L90-i Series

This gives you huge flexibility, as you can use the TM-L90-i with virtually any device and operating system. And as the TM-L90-i can control other Epson printers, it will enable you to add driverless printing capabilities to your existing printers.

The TM-L90-i simplifies servicing and maintenance and reduces your costs. It can be configured directly from web applications and, as it doesn't need a permanent connection to a PC or server, you need fewer pieces of equipment, cutting your energy bills and environmental impact.

### Key Features

- Driverless;
- Print directly from web browsers;
- Flexible;
- Works with most devices and OS;
- Printers Hub;
- Controls additional printers;
- Easy maintenance;
- Configure from web applications;
- Saves money;
- Cuts bills and environmental impact.



| Printing                  |                              | Weight & dimensions            |           |
|---------------------------|------------------------------|--------------------------------|-----------|
| Print technology *        | Direct thermal               | Width                          | 145 mm    |
| Colour *                  | ✗                            | Depth                          | 195 mm    |
| Maximum resolution *      | 180 x 180 DPI                | Height                         | 148 mm    |
| Print speed *             | 150 mm/sec                   | Weight                         | 1.6 kg    |
| Printing colours          | Black                        | Packaging data                 |           |
| Maximum printing width *  | 1.41 mm                      | Quantity per pack              | 1 pc(s)   |
| Maximum print height      | 3.39 mm                      | Package width                  | 190 mm    |
| Paper handling            |                              | Package depth                  | 250 mm    |
| Autocutter                | ✓                            | Package height                 | 240 mm    |
| Maximum roll diameter     | 9 cm                         | Package weight                 | 2.8 kg    |
| Autocutter durability     | 2000000 million cuts         | Packaging content              |           |
| Ports & interfaces        |                              | AC adapter included            | ✓         |
| Connectivity technology * | Wired                        | Logistics data                 |           |
| Wi-Fi *                   | ✗                            | Products per pallet layer      | 16 pc(s)  |
| USB port *                | ✓                            | Products per pallet layer (UK) | 24 pc(s)  |
| USB 2.0 ports quantity    | 1                            | Products per pallet (UK)       | 168 pc(s) |
| RS-232 ports              | 1                            | Pallet length (UK)             | 120 cm    |
| Performance               |                              | Pallet width (UK)              | 100 cm    |
| Print head life           | 150000000 million characters | Pallet height (UK)             | 179.5 cm  |
| Certification             | TÜV, CE                      | Harmonized System (HS) code    | 84433210  |
| Design                    |                              | Pallet gross width             | 80 cm     |
| Product colour *          | Grey                         | Pallet gross length            | 120 cm    |
|                           |                              | Pallet gross height            | 179.5 cm  |
|                           |                              | Products per pallet            | 112 pc(s) |

| Operational conditions            |            | Other features     |                 |
|-----------------------------------|------------|--------------------|-----------------|
| Operating relative humidity (H-H) | 5 - 45%    | Buffer size        | 4 KB            |
| Storage relative humidity (H-H)   | -10 - 50%  | Country of origin  | China           |
| Operating temperature (T-T)       | 10 - 90 °C | Cabling technology | 10/100Base-T(X) |
| Storage temperature (T-T)         | 10 - 90 °C |                    |                 |



8715946533568

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.