Canon

Canon imageFORMULA P-208 II Sheet-fed scanner 600 x 600 DPI A4 Black

Product family: Brand: Canon

imageFORMULA

Product code: 9704B007

Product name: P-208 II

CMOS CIS, 600dpi, RGB LED, Duplex, 8ppm/16ipm, USB 2.0, 600g, Black Canon imageFORMULA P-208 II. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, Output colour depth: 24 bit. Scanner type: Sheet-fed scanner, Product colour: Black. Sensor type: CMOS CIS, Daily duty cycle (max): 100 pages, Light source: RGB LED. Auto document feeder (ADF) input capacity: 10 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Plain paper, ISO A-series sizes (A0...A9): A4



Scanning		Ports & interfaces	
Maximum scan size *	216 x 356 mm	USB port *	✓
Optical scanning resolution *	600 x 600 DPI	USB version	2.0
Colour scanning	✓	Standard interfaces	USB 2.0
Duplex scanning *	2417	Network	
Output colour depth	24 bit	Wi-Fi	✓
Film scanning	X 256	Power	
Greyscale levels ADF scan speed (b/w, A4)	8 ppm	Power supply type *	USB
ADF scan speed (colour, A4)	8 ppm	Power consumption (typical)	2.5 W
Duplex ADF scan speed (b/w, A4)	16 ipm	Power consumption (standby)	1.5 W
Duplex ADF scan speed (colour, A4)	•	Power consumption (off)	0.5 W
Design		Input voltage	5 V
Scanner type *	Sheet-fed scanner	Weight & dimensions	
Product colour *	Black	Width	312.5 mm
Performance		Depth	56.5 mm
Sensor type *	CMOS CIS	Height	40 mm
Light source	RGB LED 100 pages	Weight	600 g
Daily duty cycle (max) *		Packaging content	
Scan drivers	ISIS, TWAIN	Drivers included	✓
Input capacity Auto document feeder (ADF) input	10 sheets	Bundled software	CaptureOnTouch CaptureOnTouch Lite Presto! BizCard Reader Evernote, SharePoint, Google Docs
capacity	TO Sheets	Sustainability	
Paper handling		Sustainability certificates	ENERGY STAR
Scanning media types supported	Plain paper A4	System requirements	
Maximum ISO A-series paper size *		Windows operating systems	
ISO A-series sizes (A0A9)	A4	supported	1
Auto Document Feeder (ADF) media weight	52 - 209 g/m²	Mac operating systems supported	✓
		Operational conditions	
		Operating temperature (T-T)	10 - 32.5 °C
		Operating relative humidity (H-H)	25 - 80%
		Other features	
		Compliance certificates	RoHS





013803247329

0013803247329

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.