



## Lindy 47731 networking cable Red 0.5 m Cat6 S/FTP (S-STP)

**Brand :** Lindy

**Product code:** 47731

**Product name :** 47731

0.5m Cat.6 S/FTP Network Cable, Red

[Lindy 47731 networking cable Red 0.5 m Cat6 S/FTP \(S-STP\):](#)

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Blue, Red, Green, Yellow, Black, White, Orange, Purple, Grey.



### Features

Product colour *	Red
Cable length *	0.5 m
Cable standard *	Cat6
Cable shielding *	S/FTP (S-STP)
Connector 1 *	RJ-45
Connector 2 *	RJ-45
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector contacts plating	Nickel/Gold
Connector shielding	✓
Connector shield material	Aluminium
Jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper
Cable class	E
Cabling technology	10/100/1000Base-T(X)
AWG wire size	27

### Features

Frequency	250 MHz
Bend radius (min)	7.4 cm

### Operational conditions

Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C

### Certificates

Certification	RoHS, REACH, UL, California Proposition 65
---------------	--

### Weight & dimensions

Outer diameter	6.2 mm
Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm

### Packaging data

Package type	Polybag
--------------	---------

### Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888477314

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.