Epson TM-T70II (022A1): UB-E04 + Built-in USB, PS, EDG, Buzzer, EU

Brand : Epson

Product code: C31CD38022A1

Product name : Epson TM-T70II (022A1): UB-E04 + Built-in USB, PS, EDG, Buzzer, EU

- Front operation: Front loading paper feed
- Fast print speeds: Up to 250mm per second
- Small footprint: Easily fits under most counters
- Greyscale printing: Add logos and images to materials
- Eco-friendly: ENERGY STAR qualified

Epson TM-T70II (022A1): UB-E04 + Built-in USB, PS, EDG, Buzzer, EU

Epson TM-T70II (022A1): UB-E04 + Built-in USB, PS, EDG, Buzzer, EU. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired, USB connector: USB Type-B, Standard interfaces: Ethernet, USB 2.0. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.7 million cuts. Product colour: Grey

Printing

Colour	✗
Maximum resolution	180 x 180 DPI
Print speed	250 mm/sec
Print speed (receipt)	250 mm/sec
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	80 mm

Ports & interfaces

USB port *	✔
USB connector	USB Type-B
Connectivity technology *	Wired
Standard interfaces	Ethernet, USB 2.0

Network

Ethernet LAN *	✔

Features

Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	360000 h
Half-cutter	✔
Autocutter durability	1.7 million cuts
Print head life	120 km
Country of origin	China
Safety	DE, TÜV, GOST-R
Certification	CE, GOST-R, EN55022-Class A

Design

Product colour *	Grey

Power

Power plug type	Type C
Power supply type	AC
Power consumption	100 mA

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	125 mm
Depth	194 mm
Height	114 mm
Weight	1.7 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	195 mm
Package depth	255 mm
Package height	245 mm
Package weight	2.86 kg

Print technology

Column capacity	56/42

Logistics data

Harmonized System (HS) code	84433210

Technical details

Changeable interface	✔

Other features

Buffer size	4 KB

Power

Power source type *	AC
AC input voltage	24 V

Other features

Electromagnetic compatibility	CE marking, GOST-R, EN55022 Class A
Mean cycles between failures (MCBF)	65000000
Print head life	120 Impulse

8715946620480

Catalog Object Cloud