

Epson TM-T88VI-iHub 180 x 180 DPI Wired Direct thermal POS printer



Brand : Epson

Product code: C31CE94751

Product name : TM-T88VI-iHub

Intelligent receipt printer, Thermal line printing, 350 mm/sec, ANK, 180 DPI

Epson TM-T88VI-iHub. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Media thickness: 0.05 - 0.08 mm. Connectivity technology: Wired, USB connector: USB Type-B, Serial interface type: RS-232. Internal memory: 512 MB, Flash memory: 512 MB, Mean time between failures (MTBF): 350000 h. Product colour: Black

| Printing | | Power | |
|-----------------------------------|------------------------|-----------------------------------|---|
| Maximum resolution | 180 x 180 DPI | AC input voltage | 24 V |
| Print speed | 350 mm/sec | Operational conditions | |
| Character size | 1.41 x 3.93 mm | Operating temperature (T-T) | 5 - 45 °C |
| Character density | 18 cpi | Operating relative humidity (H-H) | 10 - 90% |
| Printing characters | Text, Graphic, Barcode | System requirements | |
| Character sets | ANK | Pre-installed software | Device Data Notification, Server Direct Print, Webserver, ePOS-Device, ePOS-Display, ePOS-Print |
| Print technology * | Direct thermal | Weight & dimensions | |
| Type * | POS printer | Width | 145 mm |
| Paper handling | | Depth | 195 mm |
| Maximum roll diameter | 8.3 cm | Height | 148 mm |
| Supported paper width | 80 mm | Weight | 1.6 kg |
| Media thickness | 0.05 - 0.08 mm | Packaging data | |
| Ports & interfaces | | Quantity per pack | 1 pc(s) |
| USB port * | ✓ | Package width | 195 mm |
| USB 2.0 ports quantity | 4 | Package depth | 240 mm |
| USB connector | USB Type-B | Package height | 235 mm |
| Serial interface * | ✓ | Package weight | 2.62 kg |
| Serial interface type | RS-232 | Packaging content | |
| Connectivity technology * | Wired | AC adapter included | ✓ |
| Near Field Communication (NFC) | ✓ | Print technology | |
| Ethernet LAN (RJ-45) ports | 1 | Column capacity | 58/80 |
| Standard interfaces | NFC, RS-232, USB 2.0 | Logistics data | |
| Network | | Pallet weight (UK) | 0 g |
| Ethernet LAN * | ✓ | Harmonized System (HS) code | 84433210 |
| Wi-Fi * | ✗ | Products per master (outer) case | 4 pc(s) |
| Features | | Master (outer) case width | 400 mm |
| Internal memory * | 512 MB | Master (outer) case length | 490 mm |
| Flash memory | 512 MB | Master (outer) case height | 255 mm |
| Mean time between failures (MTBF) | 350000 h | Master (outer) case gross weight | 0 g |
| Cutter | ✓ | | |
| Half-cutter | ✓ | | |

| Features | | Logistics data | |
|--------------------------|---|-------------------------------------|---------------------|
| Autocutter durability | 3 million cuts | Products per pallet | 128 pc(s) |
| Built-in processor | ✓ | Products per pallet layer | 16 pc(s) |
| Processor family | Cortex-A5 | Pallet gross width | 80 cm |
| Processor frequency | 0.384 GHz | Pallet gross length | 120 cm |
| Print head life | 200 km | Pallet gross height | 15 cm |
| Country of origin | China | Pallet gross weight | 0 g |
| Mounting position | Horizontal/Vertical | Products per pallet (UK) | 192 pc(s) |
| Wall mountable | ✓ | Products per pallet layer (UK) | 24 pc(s) |
| Ribbon life | 20 million characters | Pallet width (UK) | 100 cm |
| Built-in sensors details | Paper Near End Sensor, Cover Open Sensor, Papier-Sensor | Pallet length (UK) | 120 cm |
| | CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11 | Pallet height (UK) | 15 cm |
| Certification | | Technical details | |
| | | Lifetime | 20000000 lines |
| Design | | Other features | |
| Product colour * | Black | Paper dimensions | 58 / 80 |
| Power | | Mean cycles between failures (MCBF) | 70000000 |
| Power source type * | AC | Print head life | 200.000.000 Impulse |



8715946638119

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.