

APC SMT750RM2UC uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 500 W 6 AC outlet(s)



Brand : APC Product code: SMT750RM2UC


Product name: SMT750RM2UC



Smart-UPS 750VA, RM 2U, 120V with SmartConnect
APC SMT750RM2UC. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power:
500 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s).
Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h.
Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS,
Certification: CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH

Features		Design	
UPS topology * Line-Interactive Output power capacity * 0.75 kVA Output power * 500 W Waveform * Sine Input operation voltage (min) * 82 V Input operation voltage (max) * 114 V Input frequency * 50/60 Hz	0.75 kVA 500 W Sine 82 V	Form factor * Rack capacity Cable length Product colour * Display type LED indicators	Rackmount 2U 2.44 m Black LCD Status
	out operation voltage (min) 110 V 127 V 127 V 50/60 Hz matic Voltage Regulation (AVR) ge energy rating 680 J I time (min) 6 ms	Operational conditions	
Output operation voltage (min) Output operation voltage (max) Output frequency Automatic Voltage Regulation (AVR) Surge energy rating Hold time (min)		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 90% 0 - 95% 0 - 3000 m 0 - 15000 m
Hold time (max) Noise level	10 ms 41 dB	Certificates	
Surge protection Audible alarm(s) Audible alarm modes	✓ ✓ Alarm when on battery, Low battery	Compliance certificates Certification	RoHS CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH
Auto-restart	alarm 🗸	Packaging content	
Ports & interfaces	•	Rack mount kit	✓
AC outlet types Power plug AC outlets quantity USB port	NEMA 5-15R NEMA 5-15P 6 AC outlet(s)	Cables included Quick installation guide Sustainability Sustainability certificates	RS-232, USB cable ENERGY STAR
Serial interface	✓	Weight & dimensions	
Serial interface type SmartSlot	RJ-45	Width Depth Height	432 mm 409 mm 86 mm
Battery		Weight	17.7 kg
Battery technology Number of batteries supported	Sealed Lead Acid (VRLA) 1	Packaging data	-
Battery life (max) 6 year(s) Battery recharge time 3 h Hot-swap battery ✓ Automatic battery test ✓ Cold start ✓	3 h ✓	Resource CD Software CD Package width Package depth Package height Package weight Logistics data	535 mm 570 mm 235 mm 22.6 kg
		Products per pallet	16 pc(s)

Other features	
Output voltage	120 V





731304325468

0731304325468

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.