

Epson WorkForce DS-410



Brand : Epson

Product code: B11B249401BY

Product name : Epson WorkForce DS-410

- Great productivity features at a competitive price: An outstanding scanner full of features to make your business scanning tasks efficient at an affordable price
 - 50-sheet automatic document feeder and automatic feed mode: Makes it easy to scan multiple pages, just insert the pages and the scanner will start automatically
 - Scan a versatile range of media: It can handle paper weights from 50-209gsm, plus a manual A3 mode allows ad-hoc scanning of larger-format originals
 - Protect originals and ensure every page is scanned: Intelligent and reliable paper protection technology
 - Compact and efficient addition to your business: With scan speeds of up to 26ppm and small footprint to take up little desk space
 215.9 x 3048mm, 600x600DPI, CIS, 50 - 209 g/m², 297x152x154mm, 2.5kg

Scanning		Packaging data		
Maximum scan size *	215.9 x 3048 mm	Package width	245 mm	
Optical scanning resolution *	600 x 600 DPI	Package depth	395 mm	
Colour scanning	✓	Package height	240 mm	
Duplex scanning *	✓	Package weight	3.6 kg	
Input colour depth	10 bit	Packaging content		
Output colour depth	8 bit	Cables included	AC, USB	
ADF scan speed (b/w, A4)	26 ppm	Bundled software	Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro (Windows only), Epson Scan 2	
ADF scan speed (colour, A4)	26 ppm			
Design		Sustainability		
Scanner type *	Sheet-fed scanner	Sustainability certificates	ENERGY STAR	
Product colour *	Black, White	System requirements		
Built-in display *	✗	Compatible operating systems	Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12, Windows 10, Windows 10 (32/64 bit), Windows 11, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 R2 x64, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows XP	
Performance			Windows operating systems supported	✓
Sensor type *	CIS		Mac operating systems supported	✓
Scan file formats	BMP, JPG, PDF, PNG, TIFF	Server operating systems supported	Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2	
Daily duty cycle (max) *	3000 pages	Operational conditions		
Scan drivers	ISIS, TWAIN, WIA	Operating temperature (T-T)	5 - 35 °C	
Input capacity		Storage temperature (T-T)	60 - 25 °C	
Standard input capacity	50 sheets	Operating relative humidity (H-H)	15 - 80%	
Auto document feeder (ADF) input capacity	50 sheets	Storage relative humidity (H-H)	15 - 85%	
Paper handling		Other features		
Scanning media types supported	Business Card, Post Card(JPN)	Image formats supported	BMP, JPEG, TIFF, MTIFF, PNG	
Maximum ISO A-series paper size *	A4	Printer features	RGB colour dropout, Skip blank page, A3 stitching (without carrier sheet), Automatic de-skew, RGB colour enhance, Auto-rotation, Text enhancement, Barcode Recognition, Full Zonal OCR	
ISO A-series sizes (A0...A9)	A4, A5, A6			
ISO B-series sizes (B0...B9)	B5, B6			
Letter	✓			
Legal	✓			
Auto Document Feeder (ADF) media weight	50 - 209 g/m²			
Ports & interfaces				
USB port *	✓			
USB version	2.0			
Standard interfaces	USB 2.0			
Power				
Power supply type *	AC			
Power consumption (off)	0.2 W			

Power		Other features	
AC input frequency	50 - 60 Hz	Scanner features	RGB colour dropout, Skip blank page, A3 stitching (without carrier sheet), Automatic de-skew, RGB colour enhance, Auto-rotation, Text enhancement, Barcode Recognition, Full Zonal OCR
Input voltage	100 - 120 V		
Power supply	15 W		
Weight & dimensions		Box contents	CD Manual, Main unit, Power cable, Setup guide, USB cable, Warranty card
Width	297 mm		
Depth	152 mm		
Height	154 mm	Interface	USB 2.0
Weight	2.5 kg		
Packaging data		Logistics data	
Quantity per pack	1 pc(s)	Products per pallet	72 pc(s)
		Pallet gross length	120 cm
		Pallet gross width	80 cm
		Pallet gross height	2.07 m
		Products per pallet layer	9 pc(s)
		Products per pallet layer (UK)	12 pc(s)
		Products per pallet (UK)	96 pc(s)
		Pallet length (UK)	120 cm
		Pallet height (UK)	2.07 m
		Harmonized System (HS) code	84716070



8715946638713

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.