

## APC SMT1500RM2UC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1000 W 6 AC outlet(s)




Brand : APC Product code: SMT1500RM2UC

Product name: SMT1500RM2UC



Smart-UPS 1500VA, LCD, RM 2U, 120V with SmartConnect
APC SMT1500RM2UC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power:
1000 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s).
Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h.
Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS,
Certification: REACH

Features		Battery	
Output power capacity *  Output power *  Waveform *  Input operation voltage (min) *  Input operation voltage (max) *  Input frequency *  Output operation voltage (min)  Output operation voltage (max)  Automatic Voltage Regulation (AVR)  Surge energy rating	Line-Interactive  1.44 kVA  1000 W  Sine  75 V  154 V  50/60 Hz  110 V  127 V  ✓  680 J  10 ms	Battery recharge time Hot-swap battery Automatic battery test	3 h
		Cold start  Design	<b>✓</b>
		Form factor * Rack capacity Cable length Product colour * Display type LED indicators	Rackmount 2U 2.44 m Black LCD Status
EMI/RFI noise filtering	<b>✓</b>	Operational conditions	
Noise level Power protection features Audible alarm(s) Web-based management Audible alarm modes	45 dB Short circuit  ✓ ✓ Alarm when on battery, Low battery alarm, Overload alarm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Auto-restart	✓	Certificates	
Ports & interfaces  AC outlet types  Power plug  AC outlets quantity	NEMA 5-15R NEMA 5-15P 6 AC outlet(s)	Compliance certificates Certification Sustainability Customability contificates	ROHS REACH
USB port	✓	Sustainability certificates	ENERGY STAR
Serial interface SmartSlot Battery	<i>'</i>	Weight & dimensions Width Depth Height	432 mm 477 mm 86 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	26.5 kg
Number of batteries supported Battery life (max)	1 6 year(s)	Packaging data	
		Package width Package depth Package height Package weight	590 mm 610 mm 235 mm 32.1 kg
		Logistics data	
		Harmonized System (HS) code	85078000





731304322801

0731304322801

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.