



APC SMT1500RM2UC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1000 W 6 AC outlet(s)



Brand : APC

Product code: SMT1500RM2UC

Product name : SMT1500RM2UC


Smart-UPS 1500VA, LCD, RM 2U, 120V with SmartConnect

APC SMT1500RM2UC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 1000 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: REACH

Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	1.44 kVA	Hot-swap battery	✓
Output power *	1000 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	75 V	Design	
Input operation voltage (max) *	154 V	Form factor *	Rackmount
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	110 V	Cable length	2.44 m
Output operation voltage (max)	127 V	Product colour *	Black
Automatic Voltage Regulation (AVR)	✓	Display type	LCD
Surge energy rating	680 J	LED indicators	Status
Response time	10 ms	Operational conditions	
EMI/RFI noise filtering	✓	Operating temperature (T-T)	0 - 40 °C
Noise level	45 dB	Storage temperature (T-T)	-15 - 45 °C
Power protection features	Short circuit	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Web-based management	✓	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Non-operating altitude	0 - 15000 m
Auto-restart	✓	Certificates	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	NEMA 5-15R	Certification	REACH
Power plug	NEMA 5-15P	Sustainability	
AC outlets quantity	6 AC outlet(s)	Sustainability certificates	ENERGY STAR
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	432 mm
SmartSlot	✓	Depth	477 mm
Battery		Height	86 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	26.5 kg
Number of batteries supported	1	Packaging data	
Battery life (max)	6 year(s)	Package width	590 mm
		Package depth	610 mm
		Package height	235 mm
		Package weight	32.1 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304322801



731304322801

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.