



Lindy 48345 networking cable Grey 5 m Cat5e F/UTP (FTP)

Brand : Lindy

Product code: 48345

Product name : 48345

5m Cat.5e F/UTP Network Cable, Grey

[Lindy 48345 networking cable Grey 5 m Cat5e F/UTP \(FTP\):](#)

Cat.5e F/UTP PVC network cable with support for bandwidth up to 100MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.5e cable, designed for operating frequencies up to 100MHz. With its overall shielding (F/UTP) in the form of a foil, this type of cable has been used reliably for decades in many installations in the prosumer sector as well as in the professional segment, since it can easily be used for Gigabit Ethernet. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.



Features

Product colour *	Grey
Cable length *	5 m
Cable standard *	Cat5e
Cable shielding *	F/UTP (FTP)
Connector 1 *	RJ-45
Connector 2 *	RJ-45
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector contacts plating	Nickel/Gold
Connector shielding	✓
Connector shield material	Aluminium
Jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper
Cabling technology	10/100/1000Base-T(X)
AWG wire size	26
Frequency	100 MHz

Features

Bend radius (min)	6 cm
-------------------	------

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C

Certificates

Certification	RoHS, REACH, UL, California Proposition 65
---------------	--

Weight & dimensions

Outer diameter	5 mm
Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm

Packaging data

Package type	Polybag
--------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888483452

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.