



Lindy 7.5m Cat.5e U/UTP Network Cable, Grey

Brand : Lindy

Product code: 48366

Product name : 7.5m Cat.5e U/UTP Network Cable, Grey

7.5m Cat.5e U/UTP Network Cable, Grey


[Lindy 7.5m Cat.5e U/UTP Network Cable, Grey:](#)

Cat.5e U/UTP PVC network cable with support for bandwidth up to 100MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.5e cable, designed for operating frequencies up to 100MHz. The unshielded version (U/UTP) is designed in its electrophysical parameters (NExT, FExT etc.) in such a way that it can be used for Gigabit Ethernet despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m, 40m, 50m, 60m, 70m, 80m, 90m, 100m.



Features		Operational conditions	
Product colour *	Grey	Operating temperature (T-T)	-10 - 60 °C
Cable length *	7.5 m	Storage temperature (T-T)	-20 - 75 °C
Cable standard *	Cat5e	Sustainability	
Cable shielding *	U/UTP (UTP)	Doesn't contain	Halogen
Connector 1 *	RJ-45	Certificates	
Connector 2 *	RJ-45	Certification	RoHS, REACH, UL, California Proposition 65
Connector 1 gender *	Male	Weight & dimensions	
Connector 2 gender *	Male	Outer diameter	4.8 mm
Connector contacts plating	Gold	Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Jacket material	Polyvinyl chloride (PVC)	Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Conductor type	Stranded	Packaging content	
Conductor material	Copper	Quantity per pack	1 pc(s)
Cable type	Straight-through cable	Packaging data	
Cabling technology	10/100/1000Base-T(X)	Package type	Polybag
AWG wire size	26	Logistics data	
Data transfer rate	1000 Mbit/s	Harmonized System (HS) code	84733080
Frequency	100 MHz		
Bend radius (min)	5.7 cm		
Molded cable boot	✓		



4002888483667

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.