**EPSON**

# Epson TM-J7700(321) W/O MICR,WHITE, INC PSU, EU

**Brand :** Epson

**Product code:** C31CF70321

**Product name :** TM-J7700(321) W/O MICR,WHITE, INC PSU, EU

- Versatile inkjet POS printer: Faster, better quality and more versatile
- Low TCO: Similar overall costs to previous dot matrix model
- Durable prints: Print is now more resistant to water and light
- Simple maintenance: Ink and paper rolls are very easy to replace
- Backwards compatible: Crisp, clear text and glossy photos
TM-J7700(321) W/O MICR,WHITE, INC PSU, EU
Epson TM-J7700(321) W/O MICR,WHITE, INC PSU, EU. Print technology: Inkjet, Type: POS printer, Print speed: 98 mm/sec. Supported paper width: 58 - 83 mm, Media thickness: 0.06 - 0.09 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired, USB connector: USB Type-B. Ethernet LAN data rates: 10,100 Mbit/s. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 180000 h, Autocutter durability: 1.5 million cuts

## Printing

| | |
|---|---|
| Colour | ✗ |
| Print speed | 98 mm/sec |
| Print speed (graphic) | 98 mm/sec |
| Print speed (receipt) | 98 mm/sec |
| Print speed (slip) | 85 mm/sec |
| Printing characters | Text, Graphic, Barcode |
| Character sets | ANK |
| Alphanumeric memory | 95 |
| Print technology * | Inkjet |
| Type * | POS printer |

## Paper handling

| | |
|---|---|
| Supported paper width | 58 - 83 mm |
| Media thickness | 0.06 - 0.09 mm |
| Maximum paper size (slip) | 230 x 297 mm |

## Ports & interfaces

| | |
|---|---|
| USB port * | ✔ |
| USB 2.0 ports quantity | 1 |
| USB connector | USB Type-B |
| Connectivity technology * | Wired |
| Ethernet LAN (RJ-45) ports | 1 |

## Network

| | |
|---|---|
| Ethernet LAN * | ✔ |
| Ethernet LAN data rates | 10,100 Mbit/s |
| Wi-Fi * | ✗ |

## Features

| | |
|---|---|
| Sound pressure level (printing) | 55 dB |
| Mean time between failures (MTBF) | 180000 h |

## Features

| | |
|---|---|
| Certification | CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11 |

## Design

| | |
|---|---|
| Product colour * | Black |

## Power

| | |
|---|---|
| Power source type * | DC |
| AC input voltage | 24 V |
| Power consumption (standby) | 70000 mA |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 10 - 35 °C |
| Storage temperature (T-T) | -20 - 40 °C |
| Operating relative humidity (H-H) | 20 - 80% |
| Storage relative humidity (H-H) | 20 - 85% |

## Weight & dimensions

| | |
|---|---|
| Width | 251 mm |
| Depth | 260 mm |
| Height | 188 mm |
| Weight | 5.8 kg |

## Packaging data

| | |
|---|---|
| Cables included | AC |
| Quantity per pack | 1 pc(s) |
| Package width | 355 mm |
| Package depth | 390 mm |
| Package height | 310 mm |
| Package weight | 7.87 kg |

## Features

| | |
|---|---|
| Half-cutter | ✗ |
| Autocutter durability | 1.5 million cuts |
| Country of origin | China |
| Printer receipt unit life | 3700000000 lines |
| Printer slip unit life | 5000000 lines |
| Safety | TÜV, TÜV (EN60950-1) |

## Logistics data

| | |
|---|---|
| Pallet weight (UK) | 0 g |
| Harmonized System (HS) code | 84433210 |
| Products per pallet | 36 pc(s) |
| Pallet gross weight | 0 g |
| Products per pallet (UK) | 36 pc(s) |

## Technical details

| | |
|---|---|
| Font styles | ANK |

## Other features

| | |
|---|---|
| Paper dimensions | 58 mm - 83 mm |
| Mean cycles between failures (MCBF) | 5000000 |

**8715946639079**

**Catalog Object Cloud**