



APC SMC1500C uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 900 W 8 AC outlet(s)

Brand : APC

Product code: SMC1500C

Product name : SMC1500C

- Cold-start capable
 - Green mode
 - High online efficiency
 - LCD Status Display
 - Pure sine wave output on battery
 - Temperature-compensated battery charging
- 900 W, 120V, 50/60Hz, 8x NEMA 5-15R, USB, LCD, 219x171x439 mm

APC SMC1500C uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 900 W 8 AC outlet(s):

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
APC SMC1500C. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 900 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CSA, CSA C22.2 No. 107.1, ENERGY STAR V1.0 (USA), FCC 15 B, ICES-003, UL 1778



Features		Battery	
UPS topology *	Line-Interactive	Replacement battery cartridge	RBC6
Output power capacity *	1.44 kVA	Design	
Output power *	900 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	85 V	Product colour *	Black
Input operation voltage (max) *	136 V	Display type	LCD
Input frequency *	50/60 Hz	Operational conditions	
Output operation voltage (min)	110 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	127 V	Storage temperature (T-T)	-15 - 45 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	680 J	Storage relative humidity (H-H)	0 - 95%
Hold time (min)	6 ms	Operating altitude	0 - 3000 m
Hold time (max)	10 ms	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	5%	Certificates	
EMI/RFI noise filtering	✓	Compliance certificates	RoHS
Noise level	45 dB	Certification	CSA, CSA C22.2 No. 107.1, ENERGY STAR V1.0 (USA), FCC 15 B, ICES-003, UL 1778
Surge protection	✓	Sustainability	
Audible alarm(s)	✓	Sustainability certificates	ENERGY STAR
Audible alarm modes	Low battery alarm	Weight & dimensions	
Auto-restart	✓	Width	171 mm
Ports & interfaces		Depth	439 mm
AC outlet types	NEMA 5-15R	Height	219 mm
Power plug	NEMA 5-15P	Weight	20.1 kg
AC outlets quantity	8 AC outlet(s)		
USB port	✓		

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	330 mm
Battery life (max)	5 year(s)	Package depth	590 mm
Battery recharge time	3 h	Package height	330 mm
Hot-swap battery	✓	Package weight	22.6 kg
Cold start	✓	Logistics data	
		Products per pallet	12 pc(s)
		Other features	
		Output voltage	120 V



0731304322764



731304322764

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.