



Lindy 1m USB 2.0 Type A to C Cable, Anthra Line

Brand : Lindy

Product code: 36886

Product name : 1m USB 2.0 Type A to C Cable, Anthra Line

1m USB 2.0 Type A to C Cable, Anthra Line

[Lindy 1m USB 2.0 Type A to C Cable, Anthra Line:](#)


From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A to C cables are the professional choice for high performance connections in commercial AV and IT installations.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type A to C cables are available in lengths from 0.5m to 3m.



Features		Features	
USB version *	USB 2.0	Plug and Play	✓
Connector 1 *	USB A	Nominal attenuation	0.5-3m: 0.5Mhz €" 400Mhz 5.8db
Connector 2 *	USB C	Weight & dimensions	
Connector 1 gender *	Male	Cable length *	1 m
Connector 2 gender *	Male	Cable diameter	3.5 mm
Connector 1 form factor	Straight	Bend radius (min)	3.5 cm
Connector 2 form factor	Straight	Connector 1 dimensions (WxDxH)	11 x 25.5 x 7.3 mm
AWG wire size	28	Connector 2 dimensions (WxDxH)	15.5 x 35.1 x 7.8 mm
Connector material	Gold	Packaging data	
Contact material	Phosphor bronze	Package type	Polybag
Connector contacts plating	Gold	Packaging content	
Cable jacket material	Polyvinyl chloride (PVC)	Quantity per pack *	1 pc(s)
Conductor material	Tinned copper	Operational conditions	
Connector shielding	✓	Operating temperature (T-T)	-20 - 80 °C
Connector shield material	Copper	Storage temperature (T-T)	-25 - 85 °C
Connector housing material	Polyvinyl chloride (PVC)	Certificates	
Maximum data transfer rate	480 Mbit/s	Certification	RoHS, REACH, UL
Maximum data transfer rate	0.48 Gbit/s	Logistics data	
Product colour *	Black, Grey	Harmonized System (HS) code	84733080
Cable type	Round cable		



4002888368865

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAR-2025. Prints or copies of Information are only valid on the printed Publication date