

## Lindy 1m USB 2.0 Type A to C Cable, Anthra Line

Brand: Lindy Product code: 36886

Product name: 1m USB 2.0 Type A to C Cable, Anthra

Line

1m USB 2.0 Type A to C Cable, Anthra Line

Lindy 1m USB 2.0 Type A to C Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A to C cables are the professional choice for high performance connections in commercial AV and IT installations.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain signal integrity and reliability.


Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type A to C cables are available in lengths from 0.5m to 3m.





Features		Features	
USB version *	USB 2.0	Plug and Play	✓
Connector 1 *	USB A	Nominal attenuation	0.5-3m: 0.5Mhz €" 400Mhz 5.8db
Connector 2 *	USB C	Weight & dimensions	
Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size	r* Male actor Straight 28 I Gold Phosphor bronze s plating Gold ial Polyvinyl chloride (PVC) I Tinned copper g atterial Copper material Polyvinyl chloride (PVC) asfer rate 480 Mbit/s	Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	1 m 3.5 mm 3.5 cm 11 x 25.5 x 7.3 mm 15.5 x 35.1 x 7.8 mm
Connector material Contact material		Packaging data	
Connector contacts plating		Package type	Polybag
Cable jacket material		Packaging content	
Conductor material Connector shielding		Quantity per pack *	1 pc(s)
Connector shield material		Operational conditions	
Connector housing material Maximum data transfer rate		Operating temperature (T-T) Storage temperature (T-T)	-20 - 80 °C -25 - 85 °C
Maximum data transfer rate		Certificates	
Product colour * Cable type		Certification	RoHS, REACH, UL
Cable type		Logistics data	
		Harmonized System (HS) code	84733080



4002888368865

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.