

## Lindy 1m USB 3.2 Type A to C Cable, 10Gbps, Black Line

**Brand :** Lindy **Product code:** 36916

**Product name:** 1m USB 3.2 Type A to C Cable, 10Gbps,

Black Line

- Entry level USB 3.2 Gen 2 Type A to C cable for home and small office applications
- SuperSpeed USB 10Gbps supports data transfer speeds up to 10Gbps (USB 3.1, USB 3.1 Gen 2)
- Robust PVC housing, nickel connectors, gold plated contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

1m USB 3.2 Type A to C Cable, 10Gbps, Black Line

Lindy 1m USB 3.2 Type A to C Cable, 10Gbps, Black Line. Cable length: 1 m. Connector 1: USB A, Connector 2: USB C, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 10 Gbit/s, Connector contacts plating: Gold, Product colour: Black





Features		Features	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)	Plug and Play	✓
Connector 1 *	USB A	Nominal attenuation	0.5Mhz €" 15Ghz 40db
Connector 2 * Connector 1 gender *	USB C Male	Weight & dimensions	
Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size Connector material	or 2 gender * Male or 1 form factor Straight or 2 form factor Straight re size 26/30/30	Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	1 m 4.5 mm 4.5 cm 15.5 x 35.1 x 7.8 mm 11 x 25.5 x 7.3 mm
Contact material	Phosphor bronze	Packaging data	
Connector contacts plating	Gold Polyvinyl chloride (PVC) Tinned copper  ✓ Aluminium	Package type	Polybag
Cable jacket material Conductor material		Packaging content  Quantity per pack *	1 pc(s)
Connector shielding Connector shield material		Operational conditions	
Connector housing material  Maximum data transfer rate  Maximum data transfer rate  Maximum data transfer rate  Product colour *  Cable type  Adminishm  Polyvinyl chloride (PVC)  10000 Mbit/s  10 Gbit/s  Black  Round cable	Polyvinyl chloride (PVC) 10000 Mbit/s 10 Gbit/s Black	Operating temperature (T-T) Storage temperature (T-T) Certificates Certification	-20 - 80 °C -25 - 85 °C RoHS, REACH, UL
		Logistics data	
		Harmonized System (HS) code	84733080



4002888369169

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.