

Lindy 2m USB 2.0 Type A to B Cable, Anthra Line, Grey

Brand : Lindy

Product code: 36683

Product name : 2m USB 2.0 Type A to B Cable, Anthra Line, Grey

2m USB 2.0 Type A to B Cable, Anthra Line, Grey

[Lindy 2m USB 2.0 Type A to B Cable, Anthra Line, Grey:](#)

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A to B, grey, cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

This product features a grey finish effect on the cable.

Anthra Line USB 2.0 Type A to B cables are available in lengths from 0.2m to 5m.



Features

USB version *	USB 2.0
Connector 1 *	USB A
Connector 2 *	USB B
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	26/28
Connector material	Nickel
Contact material	Copper
Connector contacts plating	Gold
Cable jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper
Connector shielding	✓
Connector shield material	Aluminium
Connector housing material	Polyvinyl chloride (PVC)
Maximum data transfer rate	480 Mbit/s
Maximum data transfer rate	0.48 Gbit/s
Cable type	Round cable
Product colour *	Grey

Features

Nominal attenuation	5.8db/km
---------------------	----------

Weight & dimensions

Cable length *	2 m
Cable diameter	4.4 mm
Bend radius (min)	1.6 cm
Connector 1 dimensions (WxDxH)	15.5 x 35 x 7.8 mm
Connector 2 dimensions (WxDxH)	11.8 x 35 x 10.2 mm

Packaging data

Package type	Polybag
--------------	---------

Packaging content

Quantity per pack *	1 pc(s)
---------------------	---------

Operational conditions

Operating temperature (T-T)	0 - 80 °C
Storage temperature (T-T)	0 - 60 °C

Certificates

Certification	RoHS, REACH, UL
---------------	-----------------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888366830

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.