Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line

Brand : Lindy

Product code: 36704

Product name : 3m USB 2.0 Type A Extension Cable, Anthra Line

3m USB 2.0 Type A Extension Cable, Anthra Line

Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A Extension cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type A Extension cables are available in lengths from 0.2m to 5m. Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line. Cable length: 3 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 2.0, Maximum data transfer rate: 0.48 Gbit/s, Connector contacts plating: Gold, Product colour: Black, Grey, Magnetically shielded



Features		Features	
USB version * Connector 1 *	inector 1 * USB A inector 2 * USB A inector 1 gender * Male inector 2 gender * Female inector 1 form factor Straight inector 2 form factor Straight	Cable type Nominal attenuation	Round cable 5.8db/km
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size		Weight & dimensions Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH)	3 m 4.4 mm 1.6 cm 15.5 x 35 x 7.8 mm
Connector materialNickelContact materialCopperConnector contacts platingGold	Connector 2 dimensions (WxDxH) Packaging data Package type	17 x 35 x 9.8 mm Polybag	
Magnetically shielded Cable jacket material Conductor material Connector shielding	 Polyvinyl chloride (PVC) Tinned copper 	Packaging content Quantity per pack * Operational conditions	1 pc(s)
Connector shield materialAluminiumConnector housing materialPolyvinyl chloride (PVC)Maximum data transfer rate480 Mbit/sMaximum data transfer rate0.48 Gbit/sProduct colour *Black, Grey	Operating temperature (T-T) Storage temperature (T-T) Certificates	0 - 60 °C 0 - 60 °C	
		Certification Logistics data Harmonized System (HS) code	RoHS, REACH, UL 84733080



4002888367042

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.