

Epson AcuLaser C3800N

Brand : Epson

Product code: C11C648001BZ

Product name : Epson AcuLaser C3800N

- Compact A4 colour laser printer
- Fast printing in colour and monochrome mode – 20 pages per minute in colour, and 25 pages per minute in B&W
- Large bright LCD panel with graphic display of job status, error message, and consumables level limit.
- Easy to integrate into existing networks, incl. multiple connection options
- 138 MB memory, expandable up to 1GB for still faster processing
- Flexible paper management with a maximum capacity of 1,250 pages and a monthly printing volume of 60,000 pages
- High resolution with Epson 4800 RIT technology
- Hi-Speed USB (2.0 compatible) and Ethernet connections
- Supports numerous printer languages: PCL6, Adobe Postscript 3 and ESC/Page Colour

Epson AcuLaser C3800N

Epson AcuLaser C3800N:

Reliability, fast, accurate printing and data safety are the main features of the new Epson AcuLaser C3800. Achieve professional high-quality results at speeds of up to 25 pages/min. in black&white, and up to 20 pages/min. in colour.



Printing		Performance	
Print speed (colour, normal quality, A4/US Letter)	20 ppm	Sound power level (standby)	30 dB
Colour *	✓	Design	
Print technology *	Laser	Market positioning *	Home & office
Duplex printing *	✗	Power	
Maximum resolution *	1200 x 1200 DPI	Power consumption (standby)	78 W
Print speed (black, normal quality, A4/US Letter) *	25 ppm	Power consumption (PowerSave)	17 W
Time to first page (black, normal)	15 s	Operational conditions	
Time to first page (colour, normal)	15 s	Operating temperature (T-T)	5 - 32 °C
Economical printing	✓	Storage temperature (T-T)	0 - 35 °C
		Operating relative humidity (H-H)	15 - 80%
Features		Sustainability	
Maximum duty cycle *	60000 pages per month	Sustainability certificates	ENERGY STAR
Number of print cartridges *	4	Weight & dimensions	
Page description languages *	PDF 1.3	Width	420 mm
Printer fonts	Barcode, Bitmap, PCL, PostScript	Height	508 mm
Number of PCL fonts	181	Weight	25.8 kg
Number of PostScript fonts	136	Dimensions (WxDxH)	420 x 501 x 508 mm
Number of bitmap fonts	15	Packaging data	
Country of origin	China	Package width	580 mm
Input & output capacity		Package depth	750 mm
Total number of input trays *	1	Package height	630 mm
Total input capacity *	150 sheets	Package weight	34.6 kg
Total output capacity *	250 sheets	Logistics data	
Maximum input capacity	1250 sheets	Pallet gross width	120 cm
Maximum output capacity	250 sheets		

Paper handling		Logistics data	
Maximum ISO A-series paper size *	A4	Pallet gross height	100 cm
Maximum print size	216 x 356 mm	Products per pallet layer	2 pc(s)
ISO A-series sizes (A0...A9) *	A4, A5	Products per pallet	6 pc(s)
ISO B-series sizes (B0...B9)	B5	Pallet length (UK)	120 cm
Non-ISO print media sizes	Executive, Legal, Letter	Pallet height (UK)	2.04 m
JIS B-series sizes (B0...B9)	B5	Products per pallet layer (UK)	2 pc(s)
Paper tray media weight	60 - 216 g/m ²	Products per pallet (UK)	6 pc(s)
Media weight (tray 1)	60-216 gsm	Other features	
Network		Non-operating relative humidity (non-condensing)	15 - 85%
Network ready	✓	Mac compatibility	✓
Supported network protocols (IPv4)	TCP/IP: LPR, FTP, IPP, PORT2501, PORT9100; NetBIOS over TCP/IP, NetBIOS over NetBEUI; Netware: Standby, NDS Print Server, Bindery Print Server, Remote Printer; AppleTalk	Standard media sizes	GLT, HLT, GLG, C5, DL
	TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SSDP, SLP; Microsoft Network: AutoIP, SSDP; NetBEUI: SNMP, SSDP; NetWare, AppleTalk: SNMP, EMPC	Power requirements	220V - 240V ±10% / 50Hz / 60Hz ± 3Hz / 4.0 A
Management protocols		Electromagnetic compatibility	EMC Directive 89/336/EEC EN 55022 Class B, EN 55024, EN 61000-3-2; EN 61000-3-3, JBMIA
		Standard input trays	1 x 150 + 1 x 550
Performance		Networking features	10/100 Base Tx
		Power consumption (active)	361 W
Internal memory *	128 MB	Safety	73/23/EEC EN 60950, EN60825-1, OSHA, TSCA, EINECS
Maximum internal memory	1024 MB	Compatible operating systems	Mac OS 10.3+, Windows 2000, Windows XP
Built-in processor	✓	Emulations	PCL5c, PCL6, ESC/P2, ESC/Page, ESC/Page-Colour, PostScript 3, PDF 1.3, FX, I239X
Processor model	PowerPC 750FL	Fonts included	✓
Processor frequency	600 MHz	Print speed	25 Pages/min Monochrome single-sided, 20 pages/min colour single-sided
Sound pressure level (printing)	51 dB	Quantity per pack	1 pc(s)



8715946328294

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.