Epson TM-T20III (011): USB + Serial, PS, Blk, EU

Brand : Epson

Product name : Epson TM-T20III (011): USB + Serial, PS, Blk, EU

Product code: C31CH51011

- Economical: Automatic paper reduction function
- Reliable: Mechanism life of 15 million lines
- Fast print speed: Print speed of 250mm/sec
- Flexible connectivity: Two models: 1) USB + Serial 2) Ethernet
- Peace of mind: Epson is Europe's number one POS printer manufacturer{s1

Epson TM-T20III (011): USB + Serial, PS, Blk, EU

Epson TM-T20III (011): USB + Serial, PS, Blk, EU. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired, USB connector: USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: Black

Printing

Maximum resolution	203 x 203 DPI
Print speed	250 mm/sec
Character density	22.6 cpi
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	80 mm

Ports & interfaces

USB port *	✔
USB 2.0 ports quantity	1
USB connector	USB Type-B
Serial interface *	✔
Serial interface type	RS-232
Connectivity technology *	Wired
Serial ports quantity	1
Standard interfaces	RS-232, USB 2.0

Network

Ethernet LAN *	✘
Wi-Fi *	✘

Features

Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	360000 h
Cutter	✔
Half-cutter	✔
Autocutter durability	1.5 million cuts
Paper save function	✔
Print head life	150 km
Country of origin	Philippines
Mounting position	Horizontal/Vertical
Wall mountable	✔

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	140 mm
Depth	199 mm
Height	146 mm
Weight	1.7 kg

Packaging data

Cables included	AC
Quantity per pack	1 pc(s)
Package width	192 mm
Package depth	235 mm
Package height	280 mm
Package weight	2.62 kg

Packaging content

Drivers included	✔
Quick start guide	✔
AC adapter included	✔

Print technology

Column capacity	48/64

Logistics data

Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per master (outer) case	4 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	295 mm
Master (outer) case gross weight	0 g
Products per pallet	112 pc(s)
Products per pallet layer	16 pc(s)
Pallet gross weight	0 g
Products per pallet (UK)	168 pc(s)

Features

Built-in sensors details	Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor
Safety	UL, CSA, TÜV
Certification	FCC-Class A, CE, EN55022-Class A

Design

Product colour *	Black

Power

Power source type *	AC
AC input voltage	24 V
Power consumption	1800 mA
Power consumption (standby)	100 mA

Logistics data

Products per pallet layer (UK)	24 pc(s)

Technical details

Lifetime	15000000 lines

Other features

Buffer size	4 KB
Mean cycles between failures (MCBF)	60000000
Print head life	150.000.000 Impulse
Print head life	150 million characters

8715946669649

Catalog Object Cloud