Brother TD-4750TNWB label printer Direct thermal / Thermal transfer 300 x 300 DPI 152 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth

Brand : Brother

Product name : TD-4750TNWB

Product code: TD-4750TNWB

- Ease of use with 2.3" colour LCD display
- Thermal transfer and direct thermal printing technology
- Range of connectivity options including USB, Network, WiFi and Bluetooth
- High capacity with 300m ribbon, minimising downtime
- 300dpi high resolution printing for crisp text and barcodes
- Fast print speeds up to 6 inches per second
4" desktop printer for high-quality, continuous label printing

Brother TD-4750TNWB label printer Direct thermal / Thermal transfer 300 x 300 DPI 152 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth:

The TD-4750TNWB versatile thermal label printer uses high capacity thermal transfer ink ribbons for durable labelling and ultimate productivity. Seamlessly integrate into your existing systems with industry standard printer command languages.
Brother TD-4750TNWB. Print technology: Direct thermal / Thermal transfer, Maximum resolution: 300 x 300 DPI, Print speed: 152 mm/sec. Connectivity technology: Wired & Wireless, Ethernet LAN, Wi-Fi, Bluetooth, Bluetooth version: 4.2, USB port. Product colour: Black

Printing

Print technology *	Direct thermal / Thermal transfer
Colour *	✗
Maximum resolution *	300 x 300 DPI
Print speed *	152 mm/sec
Maximum printing width *	10.5 cm
Maximum print length	11.43 m

Paper handling

Maximum label width	11.2 cm
Maximum roll diameter	12.7 cm

Ports & interfaces

Connectivity technology *	Wired & Wireless
Ethernet LAN *	✔
Wi-Fi *	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth	✔
Bluetooth version	4.2
USB port *	✔
USB 2.0 ports quantity	1
RS-232 ports	1

Performance

Internal memory	128 MB
Flash memory	128 MB

Operational conditions

Operating relative humidity (H-H)	5 - 40%
Storage relative humidity (H-H)	25 - 85%
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	10 - 90 °C

Weight & dimensions

Width	300 mm
Depth	440 mm
Height	275 mm
Weight	3.8 kg

Packaging data

Package weight	4.77 kg

Packaging content

Cables included	AC, USB
Bundled software	Bartender Ultra Lite Edition
Quick start guide	✔
AC adapter included	✔
Software development kit (SDK)	✔

Logistics data

Harmonized System (HS) code	84433210
Pallet gross height	15.2 cm
Pallet gross weight	163.2 kg
Master (outer) cases per pallet	30 pc(s)
Master (outer) cases per pallet layer	6 pc(s)
Layers per pallet	5 pc(s)
Products per pallet	30 pc(s)

Performance

Built-in barcodes	AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Code-128 Codabar Library, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, MaxiCode, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E

Design

Product colour *	Black
Built-in display	✔
Display *	LCD
Display diagonal	5.84 cm (2.3")
Colour display	✔

System requirements

Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Linux operating systems supported	✔

Technical details

Sustainability certificates	ENERGY STAR
Pallet type	800 x 1200 mm

Other features

Country of origin	Taiwan
Languages support	Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Norwegian, Portuguese, Slovenian
Spare part retention	5 year(s)

4977766800402

4977766800419

0012502657316

012502657316

Catalog Object Cloud