

## Lindy 70m C6 HDBaseT HDMI 18G & IR Extender Receiver

Brand: Lindy Product code: 38214

Product name: 70m C6 HDBaseT HDMI 18G & IR

**Extender Receiver** 


- Distributes HDMI resolutions up to 70m over Cat.6 network cable via HDBaseT technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- RS-232 and CEC pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation

70m Cat.6 HDMI 4K60, IR & RS-232 HDBaseT Receiver with PoC, Receiver Lindy 70m C6 HDBaseT HDMI 18G & IR Extender Receiver. Type: AV receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. USB connector type: Mini-USB B. Operating voltage: 24 V, Input current: 1 A. Width: 157 mm, Depth: 90 mm, Height: 20 mm. Package width: 220 mm, Package depth: 130 mm, Package height: 70 mm





Features         Ports & interfaces           Type *         AV receiver         DC-in jack         ✓           Maximum resolution *         3840 x 2160 pixels         Power           Cable types supported         Ca6         Operating voltage         24 V           Maximum transfer distance         70 m         Operating voltage         24 V           Chipset         V5010         Input current         1 A           Extended display identification data (EDID)         ✓         Operating temperature (T-T)         0 - 40 °C           Extended display identification data (EDID)         ✓         Operating temperature (T-T)         0 - 40 °C           CEC pass-through         ✓         Operating relative humidity (H-H)         20 - 60 °C           LED indicators         ✓         Operating relative humidity (H-H)         20 - 90%           Bandwidth         18 Gbit/s         Weight & dimensions         157 mm           HDCP         ✓         Width         157 mm           Material         Metal         157 mm         16 mm           HDCP version         2.2         Height         20 mm           Product colour         Black         Weight         20 mm           Ports & interfaces         1         <					
Maximum resolution *         3840 x 2160 pixels         Power           Cable types supported         Cat6         Operating voltage         24 V           Maximum transfer distance         70 m         Operating voltage         24 V           Chipset         V5010         Input current         1 A           Extended display identification data (EDID)         V5010         Operating temperature (T-T)         0 - 40 °C           CEC pass-through         V         Storage temperature (T-T)         -20 - 60 °C           LED indicators         V         Operating relative humidity (H-H)         20 - 90%           Bandwidth         18 Gbit/s         Weight & dimensions         V           HDCP         V         Width         157 mm           Material         Metal         Depth         90 mm           HDCP version         2.2         Height         20 mm           Product colour         Black         Weight         20 mm           Ports & interfaces         EF, FCC, REACH, California Proposition 65         Packaging data         220 mm           RJ-45 input ports         1         Package depth         130 mm           Number of HDMI outputs         1         Package weight         347 g           USB ports quantity	Features		Ports & interfaces		
Cable types supportedCat66PowerMaximum transfer distance70 mOperating voltage24 VChipsetVS010Input current1 AExtended display identification data (EDID)YOperating temperature (T-T)0 - 40 °CCEC pass-throughYStorage temperature (T-T)20 - 60 °CLED indicatorsYOperating relative humidity (H-H)20 - 90%Bandwidth18 Gbit/sWeight & dimensionsHDCPYWidth157 mmMaterialMetalDepth90 mmHDCP version2.2Height20 mmProduct colourBlackWeight345 gCertificationCE, FCC, REACH, California Proposition 65Packaging data220 mmPorts & interfaces1Package weight130 mmNumber of HDMI outputs1Package depth130 mmNumber of HDMI outputs1Package weight847 gUSB ports quantity1Package typeBoxUSB version2.0Package typeBoxUSB connector typeMini-USB BPackaging contentRS-232 input ports1Cables includedAC, IRRemote (IR) input1Cables includedAC, IRRemote (IR) output1Technical details	Type *	AV receiver	DC-in jack	✓	
Cable types supportedCat6Operating voltage24 VMaximum transfer distance70 mInput current1 AChipsetVS010Input current1 AExtended display identification data (EDID)✓Operating temperature (T-T)0 - 40 °CCEC pass-through✓Storage temperature (T-T)-20 - 60 °CLED indicators✓Operating relative humidity (H-H)20 - 90%Bandwidth18 Gbit/sWeight & dimensionsHDCP✓Width157 mmMaterialMetalDepth90 mmHDCP version2.2Height20 mmProduct colourBlackWeight345 gCertificationCE, FCC, REACH, California Proposition 65Package width220 mmPorts & interfacesPackage width220 mmRJ-45 input ports1Package depth130 mmNumber of HDMI outputs1Package weight847 gUSB ports quantity1Package weight847 gUSB version2.0Package typeBoxUSB connector typeMini-USB BPackage typeAC, IRRemote (IR) input1Cables includedAC, IRRemote (IR) input1Cables includedAC, IRRemote (IR) output1Technical details	Maximum resolution *	•	Power		
Maximum transfer obsaince  V5010  Extended display identification data (EDID)  CEC pass-through  LED indicators  Bandwidth  18 Gbit/s  Weight & dimensions  Width  157 mm  Material  Metal  MEDCP version  Abcording temperature (T-T)  20 - 60 °C  Width  157 mm  Metal  Metal  Metal  Metal  Metal  Metal  Metal  Depth  Depth  Depth  Depth  Weight  Weigh	Cable types supported			24.1/	
Extended display identification data (EDID)  CEC pass-through  ✓  CEC pass-through  18 Gbit/s  HDCP  Material  Metal  Metal  Metal  Metal  Mety Product colour  Black  CE, FCC, REACH, California Proposition 65  Ports & interfaces  RJ-45 input ports  RJ-57 input ports  RJ-45 input ports  RJ-45 input ports  RJ-45 inpu	Maximum transfer distance				
(EDID)     Operating temperature (T-T)     0 - 40 °C       CEC pass-through     Storage temperature (T-T)     -20 - 60 °C       LED indicators     Operating relative humidity (H-H)     20 - 90%       Bandwidth     18 Gbit/s     Weight & dimensions       HDCP     Metal     Depth     157 mm       Material     Metal     Depth     90 mm       HDCP version     2.2     Height     20 mm       Product colour     Black     Weight     345 g       Certification     CE, FCC, REACH, California Proposition 65     Packaging data     220 mm       Ports & interfaces     Package width     130 mm       RJ-45 input ports     1     Package depth     130 mm       Number of HDMI outputs     1     Package height     70 mm       USB ports quantity     1     Package weight     847 g       USB version     2.0     Package type     Box       USB connector type     Mini-USB B     Packaging content       RS-232 input ports     1     Cables included     AC, IR       Remote (IR) input     1     Acministration of the properties o	Chipset	VS010	•	1 A	
CEC pass-through  LED indicators  ✓ Operating relative humidity (H-H)  Bandwidth  18 Gbit/s  Weight & dimensions  Width  157 mm  Material  Metal  Depth  Depth  HDCP version  Product colour  Black  CE, FCC, REACH, California Proposition 65  Packaging data  Ports & interfaces  RJ-45 input ports  Number of HDMI outputs  1  Number of HDMI outputs  1  USB ports quantity  1  USB connector type  Mini-USB B  RS-232 input ports  RS-232 input ports  R-Remote (IR) input  Remote (IR) output  Metal  Metal  Metal  Metal  Depth  Weight  Mini-USB B  Meight  Weight  Meight  M	. ,	✓	-	0 - 40 °C	
LED indicators  Bandwidth  18 Gbit/s  HDCP  ✓  Material  Metal  Depth  Depth  Height  Depth  Height  Depth  Weight & dimensions  Weight  Depth  Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth Depth	CEC pass-through	✓			
HDCP  Material  Metal  Depth  Depth  Product colour  Black  CE, FCC, REACH, California Proposition 65  Packaging data  Package width  Package depth  Number of HDMI outputs  USB ports quantity  USB version  USB connector type  Mini-USB B  Remote (IR) input  Remote (IR) output  Metal  Metal  Metal  Depth  Width  157 mm  Width  157 mm  Midth  157 mm  Popth  Package depth  Package width  Package width  Package depth  Package depth  Package depth  Package height  Package weight  Package weight  Box  Package type  Box  Technical details	LED indicators	✓	3 ' ' '		
HDCP Material Metal Metal Depth Depth Product colour Product colour Black CE, FCC, REACH, California Proposition 65  Packaging data Package width Package depth Package depth Package height Package weight Package wei	Bandwidth	18 Gbit/s	Weight & dimensions		
MaterialMetalDepth90 mmHDCP version2.2Height20 mmProduct colourBlackWeight345 gCertificationCE, FCC, REACH, California Proposition 65Packaging dataPorts & interfacesPackage width220 mmRJ-45 input ports1Package depth130 mmNumber of HDMI outputs1Package height70 mmUSB ports quantity1Package weight847 gUSB version2.0Package typeBoxUSB connector typeMini-USB BPackaging contentRS-232 input ports1Cables includedAC, IRRemote (IR) input1Manual✓Remote (IR) output1Technical details	HDCP	✓	-	157 mm	
HDCP version Product colour Black CEF, FCC, REACH, California Proposition 65  Packaging data  Package width Package depth Package height Package weight Package weight Package weight Package weight Package weight Package veight Package veight Package veight Package type Box  USB version USB connector type Mini-USB B RS-232 input ports Package included RS-232 input Package included AC, IR Manual  Technical details	Material	Metal			
Product colourBlack CE, FCC, REACH, California Proposition 65Weight345 gPackaging dataPorts & interfacesPackage width220 mmRJ-45 input ports1Package depth130 mmNumber of HDMI outputs1Package height70 mmUSB ports quantity1Package weight847 gUSB version2.0Package typeBoxUSB connector typeMini-USB BPackaging contentRS-232 input ports1Cables includedAC, IRRemote (IR) input1Manual✓Remote (IR) output1Technical details	HDCP version	2.2	•		
Certification  CE, FCC, REACH, California Proposition 65  Packaging data  Ports & interfaces  RJ-45 input ports  1 Package depth 130 mm Package height 70 mm Package weight 9ackage weight 847 g USB ports quantity 1 Package weight 9ackage type 8box  USB connector type Mini-USB B  RS-232 input ports 1 Cables included Remote (IR) output 1 Technical details	Product colour	Black	•		
RJ-45 input ports  RJ-45 input ports  1  Number of HDMI outputs  1  Package depth  Package height  70 mm  Package weight  847 g  Package weight  USB version  2.0  Package type  Box  USB connector type  Mini-USB B  RS-232 input ports  1  Cables included  AC, IR  Remote (IR) input  Remote (IR) output  Remote (IR) output  Package depth  70 mm  Package weight  847 g  Box  Package type  Box  AC, IR  Manual  ✓  Technical details	Certification				
Number of HDMI outputs  1 Package height 70 mm  1 USB ports quantity 1 USB version 2.0 Package type Box  USB connector type Mini-USB B RS-232 input ports 1 Cables included Remote (IR) input 1 Remote (IR) output  1  Package height 70 mm  847 g Box  RAC, IR  RAC, IR  Manual  Technical details	Ports & interfaces		Package width	220 mm	
USB ports quantity  USB version  USB connector type  Mini-USB B  RS-232 input ports  Remote (IR) input  Remote (IR) output  I  Package weight  Package type  Box  Packaging content  Cables included  Manual  ✓  Technical details	RJ-45 input ports	1	Package depth	130 mm	
USB version 2.0 Package type Box  USB connector type Mini-USB B Packaging content  RS-232 input ports 1 Cables included AC, IR  Remote (IR) input 1 Manual Technical details	Number of HDMI outputs	1	5 5	70 mm	
USB connector type Mini-USB B Packaging content  RS-232 input ports 1 Cables included AC, IR  Remote (IR) input 1 Manual ✓  Technical details	USB ports quantity	1	5 5	•	
RS-232 input ports 1 Cables included AC, IR  Remote (IR) input 1 Manual   Remote (IR) output 1  Technical details	USB version	2.0	Package type	Box	
Remote (IR) input 1 Manual V Remote (IR) output 1 Technical details	USB connector type	Mini-USB B	Packaging content		
Remote (IR) output 1 Technical details	RS-232 input ports	1	Cables included	AC, IR	
Technical details	· · ·		Manual	✓	
Counting to partification Dalle	Remote (IR) output	1	Technical details		
Compliance certificates Rohs			Compliance certificates	RoHS	



4002888382144

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.