

Epson TM-M30II-S (012) 203 x 203 DPI Wired Direct thermal POS printer

Brand : Epson

Product code: C31CH63012

Product name : TM-M30II-S (012)



Epson TM-M30II-S (012). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Compatible memory cards: MicroSD (TransFlash), Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h. Product colour: White



Printing		Power	
Maximum resolution	203 x 203 DPI	Power source type *	AC
Print speed	250 mm/sec	Power plug type	Type C
Print speed (receipt)	250 mm/sec	Operational conditions	
Printing characters	Text, Graphic, Barcode	Operating temperature (T-T)	5 - 45 °C
Character sets	ANK	Storage temperature (T-T)	-20 - 60 °C
Print technology *	Direct thermal	Operating relative humidity (H-H)	10 - 90%
Type *	POS printer	Storage relative humidity (H-H)	10 - 90%
Paper handling		Weight & dimensions	
Maximum roll diameter	8.3 cm	Width	140 mm
Supported paper width	58 mm - 80 mm (Breite)	Depth	214 mm
Maximum printing width	8 cm	Height	255 mm
Ports & interfaces		Weight	2.9 kg
USB port *	✓	Packaging data	
USB 2.0 ports quantity	4	Quantity per pack	1 pc(s)
USB connector	USB Type-A / USB Type-B	Package width	210 mm
Connectivity technology *	Wired	Package depth	315 mm
Network		Package height	325 mm
Ethernet LAN *	✓	Package weight	3.83 kg
Wi-Fi *	✗	Print technology	
Features		Column capacity	48/57
Card reader integrated	✓	Logistics data	
Compatible memory cards	MicroSD (TransFlash)	Pallet weight (UK)	0 g
Sound pressure level (printing)	55 dB	Harmonized System (HS) code	84433210
Mean time between failures (MTBF)	360000 h	Products per pallet	72 pc(s)
Cutter	✓	Pallet gross weight	0 g
Half-cutter	✓	Products per pallet (UK)	96 pc(s)
Autocutter durability	2.2 million cuts	Technical details	
Tablet charge & sync	✓	Font styles	ANK
Print head life	150 km	Lifetime	17000000 lines
Country of origin	Philippines	Other features	
Mounting position	Vertical	Buffer size	12 KB
Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Papier-Sensor	Mean cycles between failures (MCBF)	65000000

Design		Other features	
Product colour *	White	Print head life	150.000.000 Impulse
		Print head life	150 million characters



8715946688817

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.