



HP LaserJet Enterprise MFP M725dn

Brand : HP

Product family: LaserJet Enterprise

Product code: CF066A#B19

Product name : LaserJet Enterprise MFP M725dn



- 100-sheet ADF; Front-facing USB printing; Scan to email/PDF; Two-sided printing
 - Print, copy, scan
 - Up to 40 ppm (black)
 - Up to 1200 x 1200 dpi
- LaserJet Enterprise MFP M725dn

[HP LaserJet Enterprise MFP M725dn:](#)

Print high-quality documents on an array of paper sizes up to A3, launch one-touch workflows, and manage jobs on the desktop with touchscreen ease. Enable large-volume printing on a wide range of paper sizes – up to A3 – with a 4,600-sheet maximum input capacity.^[1] Preview and edit scanning jobs; centrally manage printing policies; safeguard sensitive business information.

HP LaserJet Enterprise MFP M725dn. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Duplex functions: Print. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, Grey

Printing		Design	
Duplex printing mode	Auto	Control type	Buttons, Touch
Print resolution black	1200 x 1200 DPI	Colour display	✓
Print technology *	Laser	Power	
Printing *	Mono printing	Power consumption (average operating)	890 W
Duplex printing *	✓	Power consumption (PowerSave)	39 W
Maximum resolution *	1200 x 1200 DPI	Power consumption (printing)	890 W
Print speed (black, normal quality, A4/US Letter) *	41 ppm	Power consumption (copying)	890 W
Print speed (black, normal quality, A3)	20 ppm	Power consumption (ready)	39 W
Duplex print speed (ISO/IEC 24734) mono	28 ipm	Power consumption (standby)	6.5 W
Time to first page (black, normal)	10 s	Power consumption (sleep)	6.5 W
Print margins (top, bottom, right, left)	2 mm	Power consumption (off)	0.3 W
Economical printing	✓	Energy Star Typical Electricity Consumption (TEC)	2.8 kWh/week
Secure printing	✓	AC input voltage	220 - 240 V
Copying		AC input frequency	50/60 Hz
Duplex copying *	✓	Brand-specific features	
Copying *	Mono copying	HP Auto-On/Auto-Off	✓
Maximum copy resolution *	600 x 600 DPI	Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in	
Copy speed (black, normal quality, A4)	41 cpm	HP Security tools	
Maximum number of copies	9999 copies		
Copier resize	25 - 400%		
Auto fit function	✓		

Scanning		Brand-specific features	
Duplex scanning *	✓		(ABT) 887111016812; (ABY) 887111016829; (ACQ) 887111016836; (B13) 888182819586; (B19) 887111016843; (BAZ) 887111016850
Scanning *	Colour scanning	HP GTIN (EAN/UPC) with options	
Optical scanning resolution *	600 x 600 DPI		
Maximum scan area	297 x 420 mm		
Scanner type *	Flatbed scanner	HP GTIN (EAN/UPC)	887111016812, 887111016829, 887111016836, 888182819586, 887111016843, 887111016850
Scan technology	CCD		
Scan to	E-mail, Network folder, USB		
Scan speed (colour)	30 ppm		
Scan speed (black)	50 ppm		
Image formats supported	JPEG, MTIFF, TIFF		
Document formats supported	PDF, XPS		
Input colour depth	24 bit		
Greyscale levels	256		
Fax		System requirements	
Faxing *	✗	Windows operating systems supported	Windows Vista x64, Windows Vista, Windows 7 x64, Windows 7, Windows 8 x64, Windows 8, Windows 10 x64, Windows 10
Features		Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, MacOS
Recommended duty cycle	5000 - 20000 pages per month	Linux operating systems supported	✓
Maximum duty cycle *	200000 pages per month	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2008 x64, Windows Server 2008, Windows Server 2012 x64, Windows Server 2012
Duplex functions *	Print	Other operating systems supported	Novell, Linux
Digital sender	✓	Operational conditions	
Number of print cartridges *	1	Operating relative humidity (H-H)	20 - 80%
Printing colours *	Black	Recommended humidity operating range	30 - 70%
Page description languages	PostScript 3, PDF 1.4, PCL 5, PCL 6	Recommended operating temperature range (T-T)	10 - 32.5 °C
Printer fonts	Scalable, TrueType, Windows, PCL, PostScript	Storage temperature (T-T)	0 - 60 °C
Number of printer fonts	105	Operating temperature (T-T)	10 - 32.5 °C
All-In-One-multitasking	✓	Certificates	
Optional functions	Fax	Certification	CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:1998+A1+A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries
Country of origin	China, Mexico	Sustainability	
Replacement cartridges	HP 14A Black LJ Toner Cartridge CF214A (~10,000 pages); HP 14X Black LJ Toner Cartridge CF214X (~17,500 pages)	Sustainability compliance	✓
HP segment	Business	Sustainability certificates	ENERGY STAR, EPEAT Silver
Input & output capacity		Sustainable technologies and materials	Mercury Free
Total number of input trays *	3	Doesn't contain	Mercury
Total input capacity *	600 sheets	Carbon footprint	
Total output capacity *	250 sheets	Total carbon footprint (kg of CO2e)	800
Paper tray 1 input capacity	100 sheets	Carbon emissions, manufacturing (kg of CO2e)	439
Paper tray 2 input capacity	250 sheets	Carbon emissions, logistics (kg of CO2e)	22
Multi-Purpose tray	✓	Total carbon emissions, w/o use phase (kg of CO2e)	328
Multi-Purpose tray input capacity	100 sheets	Weight & dimensions	
Paper input type	Paper tray, Sheetfed	Width	614 mm
Auto document feeder (ADF)	✓	Depth	649 mm
Auto document feeder (ADF) input capacity	100 sheets	Height	609 mm
Maximum number of input trays	6	Weight	54.1 kg
Maximum input capacity	4600 sheets	Packaging data	
Maximum output capacity	250 sheets	Package width	760 mm
Paper handling		Package depth	745 mm
Maximum ISO A-series paper size *	A3		
Maximum print size	308 x 465.9 mm		
Paper tray media types *	Plain paper, Bond paper, Recycled paper, Envelopes, Card stock, Labels, Transparencies, Lightweight paper, Rough paper, Letterhead		
ISO A-series sizes (A0...A9) *	A3, A4, A5		
ISO B-series sizes (B0...B9)	B4, B5, B6		
JIS B-series sizes (B0...B9)	B4, B5		
Custom media width	76.2 - 312 mm		

Paper handling		Packaging data	
Custom media length	127 - 469.9 mm	Package height	832 mm
Paper tray media weight	60 - 199 g/m ²	Package weight	68.6 kg
Envelope feeder	No	Packaging content	
Ports & interfaces		Cables included	AC
Standard interfaces	Ethernet, USB 2.0	Warranty card	✓
Direct printing *	✓	Quick installation guide	✓
USB port	✓	Bundled software	Windows Installer, HP PCL 6 discrete driver, Mac Software Link to Web (Postscript emulation driver & Installer on Web), Note: No Mac Software inbox
USB 2.0 ports quantity	3	Logistics data	
Optional connectivity	Wireless LAN	Harmonized System (HS) code	84433100
Network		Pallet gross weight	68.6 kg
Wi-Fi *	✗	Technical details	
Ethernet LAN *	✓	Box contents	HP Laserjet Enterprise MFP M725dn; HP Black Laserjet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card; Power cord; 2x250-sheet trays.
Cabling technology	10/100/1000Base-T(X)	Compliance certificates	CECP
Ethernet LAN data rates	10,100,1000 Mbit/s	General Product Safety Regulation (GPSR) URL	https://support.hp.com/gb-en/products/setup-user-guides/hp-laserjet-enterprise-mfp-m725-series/model/5197861?sku=CF066A ; https://h10032.www1.hp.com/ctg/Manual/c03381951.pdf
Security algorithms	SNMPv3, SSL/TLS, WPA2-Enterprise, EAP-PEAP, EAP-TLS	Other features	
Supported network protocols (IPv4)	AutoIP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print	Number of users	30 user(s)
Supported network protocols (IPv6)	DHCPv6, MLDv1, ICMPv6	Custom media sizes	Tray 1: 76.2 x 127 to 312 x 469.9 mm; Tray 2: 148 x 210 to 297 x 363 mm; Tray 3: 148 x 210 to 297 x 431 mm
Security features	AES 256-bit	Pallet dimensions (W x D x H)	760 x 745 x 832 mm
Mobile printing technologies	Mopria Print Service, HP ePrint, Apple AirPrint	Printer management	HP Web Jetadmin, HP Utility (Mac)
Performance		Recommended system requirements	Windows 10; Windows 8; Windows 7; Windows Vista; Windows Server 2012 (64-bit); Windows Server 2008 (32-bit/64-bit); Windows Server 2008 R2; Windows Server 2003 (SP1+); 200 MB available hard disk space. Mac OS X 10.6; OS X Lion; OS X Mountain Lion; 1 GB available hard disk space; operating system compatible hardware system requirements; CD-ROM/DVD-ROM or Internet.
Maximum internal memory	1536 MB	Compatible operating systems	Windows 10, Windows 8, Windows 7, Windows Vista, Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1+); Mac OS X v10.6, OS X Lion, OS X Mountain Lion; For the latest operating system support see: Citrix and Windows Terminal Services (http://www.hp.com/go/upd), Novell (http://www.novell.com/jprint), Linux (http://www.hplip.net), UNIX (http://www.hp.com/go/unix , http://www.hp.com/go/unixmodelscripts , http://www.hp.com/go/jetdirectunix_software), SAP device types (http://www.hp.com/go/sap/drivers , http://www.hp.com/go/sap/print), HP ePrint Mobile Driver (http://www.hp.com/go/eprintmobiledriver)
Memory slots	1	Acoustic power emissions (ready)	50 dB
Internal storage capacity	500 GB	Acoustic pressure emissions bystander (ready)	36 dB
Internal memory *	1024 MB	Typical electricity consumption (TEC) number	Blue Angel: 2.8 kWh/Week; Energy Star 3.0: 0.653 kWh/Week
Built-in processor	✓	UNSPSC-code	43212110
Processor frequency	800 MHz	All-in-one functions	Copy, Print, Scan
Sound pressure level (printing)	54 dB	Colour all-in-one functions	✗
Sound pressure level (scanning)	52 dB	Electromagnetic compatibility	CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:1998+A1+A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries
Sound power level (printing)	6.8 dB		
Design			
Product colour *	Black, Grey		
Market positioning *	Business		
Built-in display *	✓		
Display	LCD		
Display diagonal	20.3 cm (8")		



0887111016843



887111016843

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.