

Epson WorkForce DS-770II

Brand : Epson

Product family: WorkForce

Product code: B11B262401BY

Product name : WorkForce DS-770II



- An industry first with Slow Mode{s1: Scan crumpled, long or fragile documents without increasing file sizes
- Active Separation Roller System: Prevents tedious double feeds ensuring every piece of paper gets scanned
- Optional flatbed scanner conversion kit: Enables scanning of items from stamps to passports, books and more
- Auto Scan Mode: Quickly process physical documents in manageable amounts.

A3, ReadyScan LED, 600 DPI x 600 DPI, USB 3.0
 Epson WorkForce DS-770II. Maximum scan size: 215.9 x 6096 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 30 bit. Scanner type: Sheet-fed scanner, Product colour: Black, White.
 Sensor type: CIS, Daily duty cycle (max): 7000 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 100 sheets. Maximum ISO A-series paper size: A3, Paper tray media weight: 27 - 413 g/m²

Scanning		Packaging data		
Maximum scan size *	215.9 x 6096 mm	Package depth	365 mm	
Optical scanning resolution *	600 x 600 DPI	Package height	285 mm	
Duplex scanning *	✓	Package weight	4.58 kg	
Input colour depth	30 bit	Packaging content		
Output colour depth	24 bit	Bundled software	Epson Document Capture (Mac only), Epson Document Capture Pro (Windows only), Epson Scan 2, Presto! BizCard 5.6	
Output monochrome depth	8 bit			
Design		System requirements		
Scanner type *	Sheet-fed scanner	Compatible operating systems	Citrix XenApp 5.0, Citrix XenApp 6.0, Citrix XenApp 7.6 and above, Linux, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.6.8, Windows 10, Windows 10 (32/64 bit), Windows 11, Windows 7, Windows 7 x64, Windows 8, Windows 8 (32/64 bit), Windows 8 RT, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Vista, Windows Vista x64, Windows Server 2003 R2, XP Professional x64 Edition	
Product colour *	Black, White			
Built-in display *	✗			
Performance				
Sensor type *	CIS			
Light source	ReadyScan LED	Operational conditions		
Scan file formats	BMP, JPEG, PNG	Operating temperature (T-T)		5 - 35 °C
Daily duty cycle (max) *	7000 pages	Storage temperature (T-T)		-25 - 60 °C
Scan to	E-mail, FTP, Network folder, Print	Operating relative humidity (H-H)		15 - 80%
Scan drivers	ISIS, TWAIN, WIA	Storage relative humidity (H-H)		15 - 85%
Input capacity		Other features		
Auto document feeder (ADF) input capacity	100 sheets	Image formats supported		BMP, JPEG, TIFF, MTIFF, PNG
Paper handling		Weight & dimensions		
Maximum ISO A-series paper size *	A3	Width		296 mm
Paper tray media weight	27 - 413 g/m²	Height		176 mm
Ports & interfaces		Weight	3.7 kg	
USB port *	✓	Packaging data		
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Quantity per pack	1 pc(s)	

Packaging data		Other features	
Package width	250 mm		
		Printer features	RGB colour dropout, Advanced Colour Dropout / Enhance, Skip blank page, A3 stitching, Punch holes removal, Advanced editing, Automatic de-skew, Automatic multi-document recognition, RGB colour enhance, Dual Image Output (Windows only), Auto-rotation, Text enhancement, Edge fill, Unsharp Mask (USM), Descreening, Automatic Folder Creation, Barcode Recognition, Zonal OCR A & B support, Full Zonal OCR
		Scanner features	RGB colour dropout, Advanced Colour Dropout / Enhance, Skip blank page, A3 stitching, Punch holes removal, Advanced editing, Automatic de-skew, Automatic multi-document recognition, RGB colour enhance, Dual Image Output (Windows only), Auto-rotation, Text enhancement, Edge fill, Unsharp Mask (USM), Descreening, Automatic Folder Creation, Barcode Recognition, Zonal OCR A & B support, Full Zonal OCR
		Box contents	Driver and utilities, Main unit, Power cable, Setup guide, USB cable, Warranty document
		Interface	USB 3.2 Gen 1x1
Logistics data			
		Products per pallet	63 pc(s)
		Country of origin	Indonesia
		Products per pallet (UK)	84 pc(s)



8715946685977

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.