

Lindy USB 3.2 Gen 2 Type C Docking Station

Brand: Lindy Product code: 43319

Product name: USB 3.2 Gen 2 Type C Docking Station

- Connects to a tablet, MS Surface or Ultrabook via USB Type C cable
- Adds 3 USB Type A ports (2x USB 3.2 Gen 2 up to 10Gbps, 1x USB 2.0), a USB Type C port for data and Power Delivery, an HDMI and a Gigabit Ethernet port
- Conveniently attaches to your tablet/ultrabook using a streching arm design
- Supports resolutions up to 4K Ultra HD 30Hz

USB 3.2 Gen 2 Type C Mini Docking Station - HDMI, PD 3.0 100W, USB 3.2 Gen 2, Gigabit Lindy USB 3.2 Gen 2 Type C Docking Station. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 1000 Mbit/s. Product colour: Black, Data transfer rate: 0.48 Gbit/s, Maximum digital resolution: 3840 x 2160 pixels. Power source type: USB, Output voltage: 20 V, Output current: 5 A. Width: 223 mm, Depth: 32 mm, Height: 33 mm





| Ports & interfaces | | Power | |
|---|--|---|--------------------|
| Connectivity technology * Host interface * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-C | Wired USB 3.2 Gen 1 (3.1 Gen 1) Type-C 3 | Power source type Output voltage Output current | USB 20 V 5 A |
| | | Operational conditions | |
| ports quantity | 1 | Operating temperature (T-T) | -20 - 70 °C |
| USB Power Delivery (USB PD) | ✓ | Storage temperature (T-T) | -20 - 85 °C |
| USB Power Delivery up to | 100 W | Operating relative humidity (H-H) | 20 - 80% |
| HDMI ports quantity * | 1 | Weight & dimensions | |
| HDCP version | 1.4/2.2 | Width | 223 mm |
| HDCP version | 1.4/2.2 | Depth | 32 mm |
| Network | | Height | 33 mm 160 g |
| Ethernet LAN * | / | Weight | 160 g |
| Ethernet LAN (RJ-45) ports | 1 | Packaging data | |
| Ethernet LAN data rates | 1000 Mbit/s | Package width | 280 mm |
| Performance | | Package depth Package height | 110 mm 45 mm |
| Data transfer rate | 0.48 Gbit/s | Package weight | 250 g |
| Maximum digital resolution Maximum refresh rate Product colour * Housing material Certification | 3840 x 2160 pixels 30 Hz Black Plastic CE, FCC, CP65 | Packaging content | |
| | | Manual | ✓ |
| | | Technical details | |
| | | Compliance certificates | REACH, RoHS |
| | | Logistics data | |
| | | Harmonized System (HS) code | 84733020 |



4002888433198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.