

Epson TM-T88VII (132): USB, Eth, PowerUSB, Buzz, Black

Brand : Epson

Product code: C31CJ57132

Product name : Epson TM-T88VII (132): USB, Eth, PowerUSB, Buzz, Black

- Reliable hardware: Backed by our tried and trusted build quality
- High performance: Max print speed 500mm/s
- Connectivity and interface options: USB, Ethernet, USB Host as standard; serial, PoweredUSB, options
- Backwards compatible: Fully compatible with the existing T88V and T88VI software
- Reduced environmental impacts: Low power consumption, support for Phenol-free paper

Epson TM-T88VII (132): USB, Eth, PowerUSB, Buzz, Black

Epson TM-T88VII (132): USB, Eth, PowerUSB, Buzz, Black. Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Printing media thickness: 48 - 80 µm, Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Optional connectivity: Wireless LAN. Sound pressure level (printing): 52 dB, Sound pressure level (standby): 52 dB, Mean time between failures (MTBF): 360000 h. Product colour: Black

| Printing | | Power | |
|-----------------------------------|--|-----------------------------------|--|
| Maximum resolution | 180 x 180 DPI | Power source type * | USB |
| Print speed | 500 mm/sec | Power consumption (printing) | 27.9 W |
| Character size | 1.41 x 3.39 mm | AC input voltage | 24 V |
| Printing characters | Text, Graphic, Barcode, 2D barcode | Power consumption | 27900 mA |
| Character sets | ANK | Power consumption (standby) | 1400 mA |
| Print technology * | Thermal | Power consumption (standby) | 1.4 W |
| Type * | POS printer | Operational conditions | |
| Paper handling | | Operating temperature (T-T) | 5 - 45 °C |
| Printing media thickness | 48 - 80 µm | Storage temperature (T-T) | -10 - 50 °C |
| Maximum roll diameter | 8.3 cm | Operating relative humidity (H-H) | 10 - 90% |
| Supported paper width | 80 mm | Storage relative humidity (H-H) | 10 - 90% |
| Media thickness | 48 - 80 mm | System requirements | |
| Ports & interfaces | | Pre-installed software | Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print |
| USB port * | ✓ | Weight & dimensions | |
| USB connector | USB Type-A / USB Type-B | Width | 145 mm |
| Connectivity technology * | Wired & Wireless | Depth | 195 mm |
| Near Field Communication (NFC) | ✓ | Height | 148 mm |
| Optional connectivity | Wireless LAN | Weight | 1.7 kg |
| Network | | Packaging data | |
| Ethernet LAN * | ✓ | Quantity per pack | 1 pc(s) |
| Features | | Package width | 195 mm |
| Sound pressure level (printing) | 52 dB | Package depth | 235 mm |
| Sound pressure level (standby) | 52 dB | Package height | 260 mm |
| Mean time between failures (MTBF) | 360000 h | Package weight | 2.2 kg |
| Autocutter durability | 3 million cuts | Print technology | |
| Paper save function | ✓ | Column capacity | 42/56 |
| Print head life | 200 km | Logistics data | |
| Country of origin | Philippines | Pallet weight (UK) | 0 g |
| Mounting position | Horizontal/Vertical | Harmonized System (HS) code | 84433210 |
| Wall mountable | ✓ | Products per pallet | 112 pc(s) |
| Built-in sensors details | Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor | Pallet gross weight | 0 g |
| Certification | CE | Products per pallet (UK) | 168 pc(s) |
| Design | | Technical details | |
| Product colour * | Black | Changeable interface | ✓ |
| | | Lifetime | 2000000 lines |

Other features

| | |
|-------------------------------------|----------|
| Buffer size | 4 KB |
| Mean cycles between failures (MCBF) | 70000000 |



8715946697123

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.