



## Lindy 5m DP to HDMI Adapter Cable with HDR

**Brand :** Lindy

**Product code:** 40928

**Product name :** 5m DP to HDMI Adapter Cable with HDR

- Connect a DisplayPort equipped device to a 4K HDMI display or projector
- Supports high quality resolutions up to 4K@60hz
- High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- Active chipset for enhanced compatibility with various graphic cards
- 2 year warranty

5m DP to HDMI Adapter Cable with HDR

Lindy 5m DP to HDMI Adapter Cable with HDR. Cable length: 5 m, Connector 1: DisplayPort, Connector 2: HDMI Type A (Standard). Compliance certificates: CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA, Certification: California Proposition 65. Cable diameter: 5 mm, Connector 1 dimensions (WxDxH): 36 x 20 x 7.5 mm, Connector 2 dimensions (WxDxH): 45.1 x 21.8 x 12.2 mm. Package type: Polybag. Quantity per pack: 1 pc(s)



Features		Features	
Connector 1 form factor	Straight	Cable type	Round cable
Connector 2 form factor	Straight	Connector housing material	Acrylonitrile butadiene styrene (ABS)
Connector contacts plating	Gold	Connector material	Gold
Cable length *	5 m	AWG wire size	32
Connector 1 *	DisplayPort	Cable shielding	Copper braid
Connector 2 *	HDMI Type A (Standard)	<b>Operational conditions</b>	
Connector 1 gender *	Male	Operating temperature (T-T)	-20 - 70 °C
Connector 2 gender *	Male	Storage temperature (T-T)	-25 - 85 °C
HDMI version	2.0	<b>Certificates</b>	
DisplayPort version	1.2	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
High Dynamic Range (HDR) supported	✓	Certification	California Proposition 65
Maximum resolution	4096 x 2160 pixels	<b>Sustainability</b>	
Supported graphics resolutions	4096 x 2160	Sustainability compliance	✓
Maximum refresh rate	60 Hz	<b>Weight &amp; dimensions</b>	
Refresh rate at maximum resolution	60 Hz	Cable diameter	5 mm
Bend radius (min)	6 cm	Connector 1 dimensions (WxDxH)	36 x 20 x 7.5 mm
Product colour	Black	Connector 2 dimensions (WxDxH)	45.1 x 21.8 x 12.2 mm
Conductor material	Tinned copper	<b>Packaging data</b>	
Nominal attenuation	-12dB@825-2475MHz -20dB@2475-4125MHz -25dB@4125-5100MHz	Package type	Polybag
Jacket material	Polyvinyl chloride (PVC)	<b>Packaging content</b>	
		Quantity per pack	1 pc(s)
		<b>Logistics data</b>	
		Warranty period	2 year(s)



4002888409285

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.